

Bulb Shape	Base	Watts	Nominal Length (in)	Order Code	Description	Case Qty	Rated Life (hrs)	Initial Lumens	Mean Lumens	Color Temp K	CRI	High Color Rendering	Energy Savings	Reduced Wattage	Meets Federal Minimum Efficiency Standards	Footnotes	Warning and Caution Notices	Additional Information
Other Diameters (continued)																		
Pg17 T17 Preheat																		
T17	Mogul Bi-Pin (G20)	82	60.0	43443	F90T17/CW/WM	12	9000	5750	5060	4100	60		\$	*		4	101	
		90	60.0	10643	F90T17/CW	12	9000	6000	5280	4100	60			*		4	101	
Power Groove Recessed Double Contact (1500mA)																		
PG17	Recessed Double Contact (R17d)	185	96.0	42666	F96PG17/CW/WM	8	12000	12700	9900	4100	60		\$	*		4	101	
		215	96.0	11009	F96PG17/CW	8	10000	14000	10915	4100	60			*		4	101	
		215	96.0	11018	F96PG17/D	8	10000	12100	9440	6500	74	☺				4	101	Daylight
T9 Circline® Lamps																		
T9	4-Pin (G10q)	20	6.5	42732	FC6T9/CW	12	12000	800	560	4100	60						101	
		22	8.25	33774	FC8T9/CW	12	12000	1100	825	4100	60						101	
		22	8.25	11026	FC8T9/D	12	12000	925	690	6500	75	☺					101	Daylight
		22	8.25	11084	FC8T9/KB	6	12000	1400	1120	3000	82	☺					104	Kitchen & Bath
		32	12.0	33890	FC12T9/CW	12	12000	1950	1460	4100	60						101	
		32	12.0	11039	FC12T9/D	12	12000	1675	1260	6500	75	☺					101	Daylight
		32	12.0	11085	FC12T9/KB	6	12000	2400	1920	3000	82	☺					104	Kitchen & Bath
		40	16.0	33893	FC16T9/CW	12	12000	2700	2030	4100	60						101	
		40	16.0	11052	FC16T9/D	12	12000	2250	1690	6500	75	☺					101	Daylight
Special Application Lamps																		
covGuard® Shatter Resistant																		
T5 High Efficiency																		
T5	Miniature Bi-Pin (G5)	14	21.6	73194	F14W/T5/830/ECO/CVG	40	20000	1310	1200	3000	85	☺				11, 13	103	
		14	21.6	73195	F14W/T5/835/ECO/CVG	40	20000	1310	1200	3500	85	☺				11, 13	103	
		14	21.6	73196	F14W/T5/841/ECO/CVG	40	20000	1310	1200	4100	85	☺				11, 13	103	
		14	21.6	73197	F14W/T5/850/ECO/CVG	40	20000	1260	1155	5000	85	☺				11, 13	103	
		28	45.2	81546	F28W/T5/830/ECO/CVG	40	20000	2813	2672	3000	85	☺				11, 13	103	
		28	45.2	81547	F28W/T5/835/ECO/CVG	40	20000	2813	2672	3500	85	☺				11, 13	103	
		28	45.2	81548	F28W/T5/841/ECO/CVG	40	20000	2813	2672	4100	85	☺				11, 13	103	
		28	45.2	81549	F28W/T5/850/ECO/CVG	40	20000	2667	2534	5000	85	☺				11, 13	103	
		28	45.2	81550	F28W/T5/865/ECO/CVG	40	20000	2319	2488	6500	85	☺				11, 13	103	
T5 High Output																		
T5	Miniature Bi-Pin (G5)	24	21.6	71000	F24W/T5/830/ECO/CVG	40	30000	1950	1853	3000	85	☺				11	103	Does not block UV
		24	21.6	70998	F24W/T5/835/ECO/CVG	40	30000	1950	1853	3500	85	☺				11	103	Does not block UV
		24	21.6	70997	F24W/T5/841/ECO/CVG	40	30000	1950	1853	4100	85	☺				11	103	Does not block UV
		24	21.6	70999	F24W/T5/850/ECO/CVG	40	30000	1850	1758	5000	85	☺				11	103	Does not block UV
		24	21.6	70996	F24W/T5/865/ECO/CVG	40	30000	1800	1710	6500	85	☺				11	103	Does not block UV
		39	33.4	70995	F39W/T5/830/ECO/CVG	40	30000	3400	3230	3000	85	☺				11	103	Does not block UV
		39	33.4	70994	F39W/T5/835/ECO/CVG	40	30000	3400	3230	3500	85	☺				11	103	Does not block UV
		39	33.4	70993	F39W/T5/841/ECO/CVG	40	30000	3400	3230	4100	85	☺				11	103	Does not block UV
		39	33.4	70991	F39W/T5/850/ECO/CVG	40	30000	3250	3088	5000	85	☺				11	103	Does not block UV
		39	33.4	70990	F39W/T5/865/ECO/CVG	40	30000	3250	3040	6500	85	☺				11	103	Does not block UV
		54	45.2	48433	F54T5/830/HO/ECO/CVG	40	30000	4850	4560	3000	85	☺				11	103	Does not block UV
		54	45.2	48436	F54T5/835/HO/ECO/CVG	40	30000	4850	4560	3500	85	☺				11	103	Does not block UV
		54	45.2	48458	F54T5/841/HO/ECO/CVG	40	30000	4850	4560	4100	85	☺				11	103	Does not block UV
		54	45.2	80311	F54T5/850/HO/ECO/CVG	40	30000	4650	4370	5000	85	☺				11	103	Does not block UV
		54	45.2	48469	F54T5/865/HO/ECO/CVG	40	30000	4650	4320	6500	85	☺				11	103	Does not block UV
		T5 High Output Watt-Miser®																
T5	Miniature Bi-Pin (G5)	51	45.2	72985	F54T5/830/WM/ECO/CVG	40	30000	4850	4560	3000	85	☺	\$	*		11	103	Does not block UV
		51	45.2	72986	F54T5/835/WM/ECO/CVG	40	30000	4850	4560	3500	85	☺	\$	*		11	103	Does not block UV
		51	45.2	72987	F54T5/841/WM/ECO/CVG	40	30000	4850	4560	4100	85	☺	\$	*		11	103	Does not block UV
		51	45.2	72988	F54T5/850/WM/ECO/CVG	40	30000	4650	4370	5000	85	☺	\$	*		11	103	Does not block UV
		51	45.2	72989	F54T5/865/WM/ECO/CVG	40	30000	4650	4320	6500	85	☺	\$	*		11	103	Does not block UV
T5 Preheat Lamps																		
T5	Miniature Bi-Pin (G5)	4	6.0	41435	F4T5/CW/CVG	24	5000	130	97	4100	60					11, 13	103	
		6	9.0	41106	F6T5/CW/CVG	24	5000	285	228	4100	60					11, 13	103	
		8	12.0	41107	F8T5/CW/CVG	24	5000	385	310	4100	60					11, 13	103	
		13	21.0	41108	F13T5/CW/CVG	24	5000	820	684	4100	60					11, 13	103	

For the most up-to-date product information, see www.gelighting.com. To convert inches to millimeters, multiply by 25.4. All footnotes, warning and caution notices found at the end of this section (page 4-32).