



# LED - Wall Pack - 18" Flood Type Fixtures

70,000 HRS Life

The Next Generation of Lighting



LED



## Specification:

- LED Driver	Constant Current
- Start Method	InstantON
- Hot Re-start	InstantON
- Universal Input Line Voltage	120-277 VAC
- Input Line Frequency	50/60 Hz
- System Life	70,000 Hrs.
- Lumen Maintenance @50,000Hrs	>85%
- Color Temperature	5000°K
- Color Rendering Index (CRI)	>75
- Minimum Operating Temperature	-40°F
- Maximum Ambient Temperature	125°F
- Power Factor	> 0.98
- Total Harmonic Distortion	< 10%
- Inrush Current Peak	< 10 Amp
- FCC Compliance	Part 18, Subp. C

## Applications, Features, and Benefits

- Aluminum cast housing powder coated
- Heat and impact resistant glass diffuser/lens
- 70,000 hrs LED driver made with long life components
- InstantON(TM) flicker-free Cold Start and Hot Re-Start
- High Power Factor, Low THD Driver
- Concealed continuous gasket seals against harmful dust, dirt, moisture and insects
- IP65 Rated for wet locations
- Up to 15 years Maintenance free operation
- Patented LED engine design with Advanced Thermal Management
- 5 Year Warranty

## Product Information

Item No.	Description	Watts	Initial Lumens	Line Voltage Supply	Line Current	Total Harmonic Distortion (THD)	Power Factor	Packaging Dimensions		
								Width	Length	Height
LED-21080FLD	LED - Wall Pack - Flood Type	80	6,400	120-277 VAC	0.69-0.30 Amp	<10%	0.98	12.0 in. 304 mm	20.0 in. 508 mm	11.0 in. 280 mm
LED-21100FLD	LED - Wall Pack - Flood Type	100	8,000	120-277 VAC	0.87-0.37 Amp	<10%	0.98	12.0 in. 304 mm	20.0 in. 508 mm	11.0 in. 280 mm

\*\* Optional Color Temperatures available: 3000°K, 4100°K

Fixture Weight = 28 lbs.

## Ordering Information

(SAMPLE NUMBER: LED-21080FLD-UNV-LD-120V-BRZ )

<b>Type</b> LED	<b>Series</b> 21 = Wall Pack	<b>Type</b> FLD = Flood Type	<b>Wattage</b> 080 = 80W 100 = 100W	<b>Voltage</b> UNV = Universal	<b>Accessories</b> LD = Light Detector / Photocell * must verify operating voltage	<b>Colors</b> BRZ = Dark Bronze * custom colors available
--------------------	---------------------------------	---------------------------------	-------------------------------------------	-----------------------------------	------------------------------------------------------------------------------------------	-----------------------------------------------------------------

NEPTUN Light, Inc.  
Questions and Comments:  
service@neptunlight.com  
Toll-Free: 1-888-735-8330

© Copyright 2012  
NEPTUN Light, Inc.

**NEPTUN**  
LIGHT®



Spec. Rev. 1-2012