
# LED - Wall Pack - 18" Semi-Cut-Off Fixtures

## **70,000 HRS Life**

# **The Next Generation of Lighting**







### **Specification:**

- LED Driver Constant Curre t - Start Method InstantON - Hot Re-start InstantON - Universal Input Line Voltage 120-277 VAC - Input Line Frequency 50/60 Hz - System Life 70,000 Hrs. - Lumen Maintenance @50,000Hrs >85% - Color Temperature 5000°K - Color Rendering Index (CRI) >75 - 40°F - Minimum Operating Temperature - Maximum Ambient Temperature 125°F - Power Factor > 0.98 - Total Harmonic Distortion < 10% - Inrush Current Peak < 10 Amp Part 18, Subp. C - FCC Compliance

### **Applications, Features, and Benefits**

- Aluminum cast housing powder coated
- Heat and impact resistant glass diffuser/lens
- -70,000 hrs LED driver made with long life components
- InstantON(TM) flicker-free Cold Start and Hot Re-Start
- High Power Factor, Low THD Driver
- Concealed continuous gasket seals against harmful dust, dirt, moisture and insects
- IP-65 Rated for wet locations
- Up to 15 years Maintenance free operation
- Patented LED engine design with Advanced Thermal Management
- 5 Year Warranty

#### **Product Information**

ltem No.	Description		Initial Lumens	Line Voltage Supply	Line Current	Total Harmonic Distortion (THD)	Power . Factor	Packaging Dimensions		
								Width	Length	Height
LED-21080SCT	LED - Wall Pack - Semi Cut Type	80	6,400	120-277 VAC	0.69-0.30 Amp	<10%	0.98	12.0 in. 304 mm	20.0 in. 508 mm	11.0 in. 280 mm
LED-21100SCT	LED - Wall Pack - Semi Cut Type	100	8,000	120-277 VAC	0.87-0.37 Amp	<10%	0.98	12.0 in. 304 mm	20.0 in. 508 mm	11.0 in. 280 mm

<sup>\*\*</sup> Optional Color Temperatures available: 3000°K, 4100°K

Fixture Weight = 28 lbs.

#### **Ordering Information**

(SAMPLE NUMBER: LED-21080SCT-UNV-LD-120V-BRZ)

Type | Series | Type | Wattage | SCT = Semi Cut-Off | 080 = 80W | 100 = 100W

Voltage UNV = Universal

Accessories
LD = Light Detector / Photocell
\* must verify operating voltage

Colors
BRZ = Dark Bronze
\* custom colors available

NEPTUN Light, Inc. Questions and Comments: service@neptunlight.com Toll-Free: 1-888-735-8330



