Page 1 of 1

WPLED13NMS

13 Watt high performance LED Wallpack with 5 conduit entry points. Equivalent to 150W MH. Includes both junction box and surface mount for recessed box. IESNA Full Cutoff, Fully shielded optics. Mount at 11-20'. 5 year warranty.

Color: Bronze Weight: 3.8 lbs



LED Info **Driver Info**

vvatts	:	13	Type:	Constant Current
Color	Temp:	4000K (Neutral)	120V:	0.13 A
Color	Accuracy:	86	208V:	0.08 A
L70 L	ifespan:	0	240V:	0.07 A
LM79	Lumens:	1,064	277V:	0.06 A
Effica	су:	71 LPW	Input Watts:	15W
			Efficiency:	87%

Technical Specifications

UL Listing:

Suitable for Wet Locations as a Downlight. Suitable for Damp Locations as an Uplight. Wall Mount only. Suitable for Mounting within 4ft. of ground.

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by IBEW Local 3

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel,_and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010)

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

This product is suitable for listing on the GSA Schedule of the US General_Services in accordance with FAR Subpart 25.4



Email: sales@rabweb.com On the web at: www.rabweb.com Note: Specifications are subject to change without notice