

## FIXTURE SPECIFICATIONS

### INTENDED USE


The integrated color-changing LED lightstrip has a 1-inch lens aperture width and is available in standard lengths of 2-foot, 4-foot, 6-foot, 8-foot and custom cuts. Our commercial-grade product with dimmable light via Android or iOS application or optional controls can be joined in seamless runs of any length. This 24-voltage lightstrip offers direct downlight secured in a military-grade, field-cutable aluminum channel.

### PRODUCT FAMILY


- 12100-10-P** | Pendant
- 12100-10-S** | Surface
- 12100-10-R** | Recessed
- 12100-10-LR** | Low-Profile Recessed
- 12100-10-PR** | Perimeter Recessed
- 12100-10-PR-RGBW** | Perimeter Recessed RGBW

### FEATURES


- Construction:** Durable military grade aluminum, field cuttable can be installed in any drywall thickness
- LED Driver:** Remote non-dimming transformer is provided home run required at every 16'
- Beam Angle:** 120°
- Lens:** Glare-free snap-in frosted acrylic for even distribution
- Shape Design:** Fixture profile can be miter cut-in the field-to achieve desired shape design
- Finish:** Matte White
- Voltage:** 24V DC Constant Voltage
- Lumens:** 547 Lm/Ft. (167 Lm. (RGB) | 380 Lm. (White))
- Wattage:** 8.8W per foot
- CRI:** 90+
- Dimming:** Light is Dimmable via iOS/Android Application or Optional Controls
- WiFi Controls (iOS/Android):** Mobile App: Easy Home Smart Home  
DMX Wall App: WiFi 104
- Life:** 50,000 Hours
- Warranty:** 5 Years Carefree for Parts & Components (Labor Not Included)
- Listings:** cUL Listed, Title 24 Certified, Dry Location IP45 (LED Component Only), Optional Wet Location IP65 (LED Component Only)



### TRIMLESS MOUNT



### T-BAR & FLANGE MOUNT



## ORDERING INFORMATION Example: (12100-10-R-RGBW-2-RGBW27K-RTL-RF)

Model	Length	Color Temp	Mount Type	Flange Finish <sup>1</sup>	Controls	DMX Decoder	Options
<b>12100-10-R-RGBW</b> Recessed RGBW	<b>2</b> 2 Foot	<b>RGBW27K</b> RGB + 2700K	<b>RTL</b> Trimless	<b>WH</b> White	<b>WiFi</b> Mobile Application + WiFi	<b>(Blank)</b> None required	<b>WL<sup>2</sup></b> Wet Location IP65
	<b>4</b> 4 Foot	<b>RGBW30K</b> RGB + 3000K	<b>RT</b> T-Bar	<b>BK</b> Black	<b>RF</b> RF Remote Control (White)	<b>DEC-4C</b> 4-Channel RJ45	
	<b>6</b> 6 Foot	<b>RGBW40K</b> RGB + 4000K	<b>RF</b> Flanged	<b>SL</b> Silver	<b>DMX</b> DMX Wall Control (White)	<b>DEC-5C</b> 5-Channel RJ45/XLR	
	<b>8</b> 8 Foot	<b>RGBW50K</b> RGB + 5000K			<b>DMX-WIFI-W</b> DMX Wall Control (White) + WiFi		
	<b>XX</b> Custom Length <small>Replace XX with Length in Feet</small>				<b>DMX-WIFI-B</b> DMX Wall Control (Black) + WiFi		


<sup>1</sup> Not required for Trimless

<sup>2</sup> Wet location option is available for the LED component only


## EXTERNAL DIMMING DRIVER SPECIFICATIONS

### Non-Dimming Driver with Junction Box


NDD-30W-24V




NDD-60W-24V




NDD-96W-24V




NDD-150W-24V



NDD-200W-24V



NDD-300W-24V



RGBW CONTROLS




**RF Remote Control**  
6.38" L x 1.65" W x 0.59" H



**Mobile Application + WiFi**



**DMX Wall Control**  
5.20" L x 7.09" W x 1.38" H



**DMX Wall Control + WiFi**



5.75" L x 4.17" W x 0.43" H

COLOR TEMPERATURE

## COLOR TEMPERATURE GUIDE



<p><b>2700K</b></p> <p><b>WARM WHITE</b></p> <p>friendly personal intimate</p> <p>HOMES LIBRARIES RESTAURANTS</p> <p>✓</p>	<p><b>3000K</b></p> <p><b>SOFT WHITE GLOW</b></p> <p>soft warm pleasing</p> <p>HOMES HOTEL ROOMS LOBBIES RETAIL STORES</p> <p>✓</p>	<p><b>3500K</b></p> <p><b>NEUTRAL GLOW</b></p> <p>sociable inviting non-threatening</p> <p>EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS</p> <p>✗</p>	<p><b>4000K</b></p> <p><b>DAYLIGHT GLOW</b></p> <p>neat clean efficient</p> <p>OFFICES CLASSROOMS MASS MERCHANDISERS SHOWROOMS</p> <p>✓</p>	<p><b>5000K</b></p> <p><b>CRYSTAL WHITE GLOW</b></p> <p>bright cool alert</p> <p>GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS</p> <p>✓</p>
--	---	--	---	---