

**FIXTURE SPECIFICATIONS**

**INTENDED USE**

The specification grade **Continuum 44 LED Wall Mount Architectural Linear Luminaire** delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish designs offer excellent illumination, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The integrated LED Continuum is available in standard lengths of 4' and 8', and can be joined together in seamless runs of any length.

**PRODUCT FAMILY**


- 12100-44-P** | Pendant Mount
- 12100-44-W** | Wall Mount
- 12100-44-S** | Surface Mount
- 12100-44-R** | Recessed Mount

**AVAILABLE LENGTHS**

- 4FT** | W 4" x L 48" x H 4"
- 8FT** | W 4" x L 96" x H 4"
- Continuous Run** | Consult Factory
- Custom Length** | Consult Factory

**FEATURES**

- Construction:** Die-Formed and Welded 22-Gauge Cold Rolled Steel
- Continuous Run:** Full Ability to Tandem Mount for Continuous Run Application, Equipped with Male & Female Quick Connect Harnesses
- Custom Design:** Offered with Pre-Fabricated and Fully Illuminated Corners
- Lens:** Glare Free Snap In Frosted Acrylic for Even Distribution
- Voltage:** 120-277V (50/60 Hz) Constant Current
- Dimming:** 5-Wire 0-10V (100%-10%), 3-Wire Electronic Low Voltage (100%-1%)
- CRI:** 80+ & 90+
- Life:** 50,000 Hours L70
- Warranty:** 5 Years Carefree for Parts & Components (Labor Not Included)
- Listings:** CA Title 24 Compliant, cETL Listed, LED Chips Tested to LM-80 Standards



**ORDERING INFORMATION** Example: (12100-44-W-D-R24-RC-8x8-27K-WH-D10-EM)

Model	Mount	Distribution	Lumen Output	Shape	Finish	Color Temp	Dimming Driver
<b>12100-44</b> 4" x 4"	<b>W</b> Wall	<b>D</b> Direct <b>I</b> Indirect <b>WW</b> Wall Wash	<b>R24</b> 24 watts   2400 lms <b>R48</b> 48 watts   4800 lms	<b>S</b> Single Unit  <b>CR</b> Continuous Run  <b>RC</b> Rectangle  <b>SQ</b> Square	<b>Standard</b> <b>WH</b> White <b>BK</b> Black <b>SL</b> Silver  <b>Premium</b> <b>RD</b> Red <b>BL</b> Blue <b>GR</b> Green <b>OR</b> Orange <b>SB</b> Satin Brass	<b>Residential</b> <b>27K<sup>1</sup></b> 2700K <b>30K</b> 3000K  <b>Commercial</b> <b>35K</b> 3500K <b>40K</b> 4000K  <b>Industrial</b> <b>50K</b> 5000K	<b>010 Standard</b> 0-10V (100-1%) <b>ELV</b> Electronic Low Voltage (100%-1%)
				<b>Total Run (in Feet)</b> 			
				<b>Width</b> <b>Length</b> 			
				<b>Width</b> <b>Length</b> 			
				<b>CU<sup>2</sup></b> Custom 			
				<b>or</b> 			
					<b>Options</b> <b>EM</b> Remote Emergency Backup Battery (4ft canopy) <b>AB<sup>2</sup></b> Independent Control of Up & Down <b>DS</b> Daylight Sensor <b>OS</b> Occupancy Sensor	<b>Controls</b> <b>Optional</b> <b>LV</b> Lutron VIVE™ Wireless <b>LE</b> Lutron EcoSystem™ <b>BM</b> Bluetooth Mesh	

Formerly: 12107 Beam 44

<sup>1</sup> 90+ CRI  
<sup>2</sup> Required for D/I Distributions Only