

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

The specification grade decorative Architectural LED Ring Light delivers continuous clean lines and clear circle light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish hanging lights designs offer excellent direct lighting, indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The ring light ring chandelier is available in multiple lengths and several finishes.

DETAILS

W 1.4" x Depth 1.1"

Standard Canopy: 10" x 2.25"

Remote Canopy: 3" x .45"

Pendant: 8' adjustable aircraft cable/power cord included (*custom length available*)

Construction: Extruded aluminum outer housing Adjustable power cord and AC cables with push button grippers standard

Lens: Opal Acrylic diffuser

Reflector: Glare-free, one piece, heavy gauge aluminum

Power Cable: Grey finish jacket

Mounting: All standard J-boxes


ADDITIONAL FEATURES

Voltage: 120/277


CRI: 90

Dimming: 0-10V, dims to 1%


Emergency: 90 minutes minimum, Remote install only




S – Standard




R – Remote



Cross Section



RD - Braided Red Architectural Cable Mount



ORDERING INFORMATION Example: [12254-2-30K-SL-WH-S-EM](#)

| Model | LED Downlight | Color Temp | Finish | Cable Finish | Mounting | Options |
|--------------|---|---------------------|---------------------|--------------------------|----------------------|---|
| 12254 | 2 2 ft 26 Watts 2166 Lumens | 30K 3000K | SL Silver | WH White | S Standard | EM 7W Emergency Battery Pack |
| | 3 3 ft 39 Watts 3250 Lumens | 35K 3500K | BK Black | GR Gray | R Remote | XX Custom AC Cable/Power Cord (25' Max) |
| | 4 4 ft 52 Watts 4333 Lumens | 40K 4000K | WH White | RD Braided Red | | |
| | 5 5 ft 65 Watts 5416 Lumens | | | | | |
| | | | | | | |

COMPATIBLE DIMMERS

| | | | |
|---------------|---|--|---|
| |  |  |  |
| 0-10 V | 2100 2101 2102 | Diva DDTV | IP-710-DL |

COLOR TEMPERATURE GUIDE



| | | | | |
|---|--|---|--|---|
| <p>2700K</p> <p>WARM WHITE</p> <p>friendly personal intimate</p> <p>HOMES LIBRARIES RESTAURANTS</p> <p>X</p> | <p>3000K</p> <p>SOFT WHITE GLOW</p> <p>soft warm pleasing</p> <p>HOMES HOTEL ROOMS LOBBIES RETAIL STORES</p> <p>✓</p> | <p>3500K</p> <p>NEUTRAL GLOW</p> <p>sociable inviting non-threatening</p> <p>EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS</p> <p>✓</p> | <p>4000K</p> <p>COOL WHITE GLOW</p> <p>neat clean efficient</p> <p>OFFICES CLASSROOMS MASS MERCHANDISERS SHOWROOMS</p> <p>✓</p> | <p>5000K</p> <p>DAYLIGHT GLOW</p> <p>bright cool alert</p> <p>GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS</p> <p>X</p> |
|---|--|---|--|---|