



**FIXTURE SPECIFICATIONS**

**INTENDED USE**

The **Illusione 3 Inch Architectural LED Square Trimless Recessed Light Fixture** is designed for lasting durability and beauty while providing quality and energy efficient lighting for low to medium ceilings. The Illusione is an ideal solution for clear and bright lighting in retail, hospitality, commercial, and high-end residential settings.

**W 3" x L 3 3/16" x H 3 1/8"**

**PRODUCT FAMILY**

- 14006** | Recessed Down Light
- 14006-2** | Open Reflector
- 14006-4** | Open Reflector Wall Wash

**FEATURES**

- Construction:** Seamless Die-Cast with IC Rated Housing with Loosefill Blown and Rolled Insulation
- Collar Bracket:** 90° Rotation in 5° Increments (Pre-Drywall Installation)
- Lamp Holder:** 35° Tilt  
1 1/2" Vertical Lamp Source Adjustment
- Mounting:** Housing for New Construction Installation Only  
(2) 24" Adjustable Hangar Bars w/ 90° Repositioning
- Beam Spread:** 45°
- Lens:** Frosted
- Power Connection:** LED Lamp Array is Replaceable via On Board Quick Disconnect Terminal
- Voltage:** 120/277 UNV
- Wattage:** 19W
- Lumens:** 1200 lms
- Dimming:** 120V/277V UNIDIM  
*Compatible with most 3-Wire ELV, 2-Wire Incandescent and 5-Wire 0-10V dimmers*
- Warm Dimming Option:** Fixture starts at 2700K Full-Brightness and Smoothly Dims to 1850K / 5%
- CRI:** 80 Standard
- Life:** 50,000 Hours
- Listings:** ETL Listed  
Title 24 / JA8 Compliant Certified by CEC



**ORDERING INFORMATION** Example: (14006-3-27K-WL)

Model	Color Temp	Options
<b>14006-3</b>	<b>27K</b> 2700K	<b>WL</b> Wet Location <b>EM</b> 5W Emergency Remote <i>(Above Ceiling Access Required)</i>
	<b>27C</b> 2700K <i>(90+ CRI)</i>	
	<b>30K</b> 3000K	
	<b>35K</b> 3500K	
	<b>40K</b> 4000K	
	<b>WD</b> Warm Dimming <i>(1850K-2700K)</i>	