



## FIXTURE SPECIFICATIONS

### INTENDED USE

The specification grade **Basic Architectural LED Recessed Troffer** fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

### PRODUCT FAMILY

**14115** | 1x4

**14116** | 2x4

### FEATURES

- Construction:** Die-formed and embossed code 22 gauge steel housing
- Access plate to simplify installation
- Finish:** High reflectance baked white enamel
- Lens:** Clear 0.10 thick A12 Acrylic
- Voltage:** 120- 277 UNV
- Support:** Recessed Inverted T-Bar Ceilings. Grid
- Mount Life:** 50,000 Hrs
- Operating Temperature:** -4°F~122°F
- Lamp Included
- Listings:** UL Listed



## ORDERING INFORMATION

Example: (14114-24W2600-30K-DM10-EM)

Model	Wattage & Lumens	Color Temp	Dimming	Options
<b>14114</b>	<b>24W2600</b> 24W   2600 lumens	<b>30K</b> 3000K <b>35K</b> 3500K	<b>ND</b> Non-Dimming <b>DM10<sup>2</sup></b> 5-Wire 0-10V Dimming (100%-10%)	<b>EM</b> Emergency Backup Battery
	<b>28W3000</b> 28W   3000 lumens	<b>40K</b> 4000K <b>50K</b> 5000K		
	<b>35W3600</b> 35W   3600 lumens		<b>DM1<sup>2</sup></b> 5-Wire 0-10V Dimming (100%-1%)	