



FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Basic Architectural LED Recessed Troffer** fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

PRODUCT FAMILY

14114 | 2x2

14116 | 2x4

FEATURES

- Construction:** Die-formed and embossed code 22 gauge steel housing
- Access plate to simplify installation
- Finish:** High reflectance baked white enamel
- Lens:** Clear 0.10 thick A12 Acrylic
- Voltage:** 120- 277 UNV
- Support:** Recessed Inverted T-Bar Ceilings. Grid
- Mount Life:** 50,000 Hrs
- Operating Temperature:** -4°F~122°F
- Lamp Included
- Listings:** UL Listed



ORDERING INFORMATION Example: (14115-35W4100-30K-DM10-EM)

Model	Wattage & Lumens	Color Temp	Dimming	Options
14115	35W4100	30K 3000K	ND Non-Dimming	EM Emergency Backup Battery
	35W 4100 lumens	35K 3500K	DM10² 5-Wire 0-10V Dimming (100%-10%)	
	48W5400	40K 4000K	DM1² 5-Wire 0-10V Dimming (100%-1%)	
	48W 5400 lumens	50K 5000K		