

2x10W | 800 lms



FIXTURE SPECIFICATIONS

INTENDED USE

The **Eve Architectural LED Dual Head Track Head** delivers energy efficient and clear light to commercial, hospitality and residential interior lighting applications. Our modern profiles and stylish designs offer excellent direct lighting and exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.





PRODUCT FAMILY ACCESSORIES

- 13002-1** | 2 FT Track Channel
- 13004-1** | 4FT Track Channel
- 13941-1** | Live End Feed Limiter
- 13991-1** | Live End Feed
- 13927-1** | T-Bar Live End Feed
- 13943-1** | L-Connector
- 13946-1** | X-Connector
- 13949-1** | Mini Connector
- 13980-1** | Conduit Connector
- 13929-1** | Floating Canopy Connector

FEATURES

- Construction:** Sleek, Durable Steel Body with Concealed Heat Sink, Wiring, and Internal Adjustment Mechanism Allowing for Maximum Adjustability
- Connector:** 3-Wire H-Type 1 Circuit & 2 Circuit Track(Standard)
- Adjustable:** 350° Rotation / 0°-180° Gimbal
- Electrical:** Integral Electronic Constant Current
- Voltage:** 120V
- Dimming:** 120V 2-Wire/Incandescent/ELV Dimming
- CRI:** 90+
- Life:** 35,000 Hours L70
- Warranty:** 3 Years Carefree for Parts & Components (Labor Not Included)
- Listings:** ETL/cETL Listed for Dry Locations Only
- Lamp Equivalents:** 2x75W MR16FL / 2x100W PAR20

2x18W | 1400 lms



ORDERING INFORMATION Example: (14132-10W-FL45-27K-WH-LV)

Model	Lumens	Beam Spread	Color Temp	Finish	Options
14132	10W	FL45 <small>Standard</small>	<small>Residential</small>	WH	LV
Cylo Swivel	2x10W 800 lms	45° Flood	27K 2700K	White	Glare-Free Louver
Cylinder	18W	SP15	30K 3000K	BK	JT ¹
(Dual Head)	2x18W 1400 lms	15° Spot	<small>Commercial</small>	Black	J-Type Connector
		NF25	35K 3500K		LT ¹
		25° Narrow Flood	40K 4000K		L-Type Connector

¹Consult Factory + Extended Lead Time