



## FIXTURE SPECIFICATIONS

### INTENDED USE

The **Infinum Architectural Commercial LED High Bay** is designed to provide high lumen output, exceptional color rendering, and ultra long life. The Infinum is an ideal option for replacing HID and fluorescent high bay systems and for commercial and industrial interiors.

### FEATURES

**Construction:** 22 Gauge Pre-Painted Steel with Air Vents to Maximize Performance, Reliability, and Life and Back Access Plate for Fast and Hassle-Free Wiring

**Lens:** Glare-Free, Diffused

**Voltage:** 100-277 VAC

**CRI:** 82+

**Life:** 80,000 Hours+ (L70)

**THD:** <10%

**Power Factor:** >0.99

**Operating Temperature:** -4°F - 122°F

**Warranty:** 10 Years on All Non-24/7 Operation

7 Years on 24/7 Operation

**Listings:** cULus Listed

Damp Location Suitable

DLC Certified at >145 Lumens/Watt



## ORDERING INFORMATION Example: (15222-3-90W-40K-010-PN-WH6-EM8-REM)

Model	Lamps, Wattage, & Lumens	Dimming	Mounting	Cord Set	Options
<b>15222</b>	<b>3-90W-40K</b> 3 Lamps   90 watts   11700 lms   4000K	<b>ND</b> Non-Dimming <b>010</b> 0-10V Dimming	<b>PN</b> Pendant <b>JC</b> Jack Chain <b>VH</b> V-Hanger	<b>WH6</b> 6 FT   3-Wire   White  <b>WH12</b> 12 FT   3-Wire   White	<b>EME</b> External Emergency Backup (850 lms)
	<b>3-90W-50K</b> 3 Lamps   90 watts   12870 lms   5000K				<b>EMI</b> Internal Emergency Backup (1100 lms)
	<b>4-120W-40K</b> 4 Lamps   120 watts   15600 lms   4000K				<b>OS</b> Occupancy Sensor
	<b>4-120W-50K</b> 4 Lamps   120 watts   17160 lms   5000K				<b>REM</b> Dimming Sensor Remote
	<b>5-150W-40K</b> 5 Lamps   150 watts   19500 lms   4000K				<b>WG</b> Wireguard
	<b>5-150W-50K</b> 5 Lamps   150 watts   21450 lms   5000K				<b>LEN</b> Lens