



FIXTURE SPECIFICATIONS

INTENDED USE

The **Infinum Architectural Commercial LED High Bay** is designed to provide high lumen output, exceptional color rendering, and ultra long life. The Infinum is an ideal option for replacing HID and fluorescent high bay systems and for commercial and industrial interiors.

FEATURES

- Construction:** 22 Gauge Pre-Painted Steel with Air Vents to Maximize Performance, Reliability, and Life and Back Access Plate for Fast and Hassle-Free Wiring
- Lens:** Glare-Free, Diffused
- Voltage:** 100-277 VAC
- CRI:** 82+
- Life:** 80,000 Hours+ (L70)
- THD:** <10%
- Power Factor:** >0.99
- Operating Temperature:** -4°F - 122°F
- Warranty:** 10 Years on All Non-24/7 Operation
7 Years on 24/7 Operation
- Listings:** cULus Listed
Damp Location Suitable
DLC Certified at >145 Lumens/Watt



ORDERING INFORMATION Example: (15222-6-180W-40K-010-PN-WH6-EM8-REM)

Model	Lamps, Wattage, & Lumens	Dimming	Mounting	Cord Set	Options
15222	6-180W-40K 6 Lamps 180 watts 23400 lms 4000K	ND Non-Dimming 010 0-10V Dimming	PN Pendant JC Jack Chain VH V-Hanger	WH6 6 FT 3-Wire White WH12 12 FT 3-Wire White	EM8 External Emergency Backup (850 lms)
	6-180W-50K 6 Lamps 180 watts 25740 lms 5000K				EM9 Internal Emergency Backup (1100 lms)
	7-210W-40K 7 Lamps 210 watts 27300 lms 4000K				OS Occupancy Sensor
	7-210W-50K 7 Lamps 210 watts 30030 lms 5000K				REM Dimming Sensor Remote WG Wireguard LEN Lens