



FIXTURE SPECIFICATIONS

INTENDED USE

The **Infinum Architectural Commercial LED High Bay** is designed to provide high lumen output, exceptional color rendering, and ultra long life. The Infinum is an ideal option for replacing HID and fluorescent high bay systems and for commercial and industrial interiors.

FEATURES

Construction: 22 Gauge Pre-Painted Steel with Air Vents to Maximize Performance, Reliability, and Life and Back Access Plate for Fast and Hassle-Free Wiring

Lens: Glare-Free, Diffused

Voltage: 100-277 VAC

CRI: 82+

Life: 80,000 Hours+ (L70)

THD: <10%

Power Factor: >0.99

Operating Temperature: -4°F - 122°F

Warranty: 10 Years on All Non-24/7 Operation
7 Years on 24/7 Operation

Listings: cULus Listed
Damp Location Suitable
DLC Certified at >145 Lumens/Watt



ORDERING INFORMATION Example: (15222-8-240W-40K-010-PN-WH6-EM8-REM)

Model	Lamps, Wattage, & Lumens	Dimming	Mounting	Cord Set	Options
15222	8-240W-40K 8 Lamps 240 watts 31200 lms 4000K	ND Non-Dimming 010 0-10V Dimming	PN Pendant	WH6 6 FT 3-Wire White	EM8 External Emergency Backup (850 lms) EM9 Internal Emergency Backup (1100 lms) OS Occupancy Sensor REM Dimming Sensor Remote WG Wireguard LEN Lens
	8-240W-50K 8 Lamps 240 watts 34320 lms 5000K		JC Jack Chain VH V-Hanger		
	9-270W-40K 9 Lamps 270 watts 35100 lms 4000K		WH12 12 FT 3-Wire White		
	9-270W-50K 9 Lamps 270 watts 38610 lms 5000K				
	10-300W-40K 10 Lamps 300 watts 39000 lms 4000K				
	10-300W-50K 10 Lamps 300 watts 42900 lms 5000K				