



FIXTURE SPECIFICATIONS

INTENDED USE

The **EMEXTH Architectural LED Thin Thermoplastic Exit Sign** features consistently bright illumination with an energy efficient, long life light. The EMEXTH is an ideal option for interiors where emergency exit lighting is needed.

FEATURES

- Construction:** Specification-Grade, Low Profile Injection-Molded, Engineering Grade, 5VA Flame Retardant, High-Impact Resistant Thermoplastic
- Electrical:** Charge Rate/Power "ON" LED Indicator Light and Push-to-Test Switch for Mandated Code Compliance Testing
- Battery:** 4.8V Long life, Maintenance-Free Rechargeable NiCd Fully Automatic Solid-State, Two Rate Charger
- Mounting:** Compatible with Drywall or Drop Ceiling Mount Installations
(Bar Hangers Included)
Wall Mount Capability Optional
- Lens:** Prismatic Polycarbonate Mirror-Bright Reflector
- Voltage:** Dual 120/277V
- Wattage:** 3.8W
- Self-Diagnostic Testing:** Continuously Diagnoses Units' Performance and Test Systems
- Warranty:** 5 Years
Battery Pro-Rated for 5 Years
- Listings:** Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local, and State Codes
UL Listed for Damp Location 32° F (0°C) - 122°F (50°C)



ORDERING INFORMATION Example: (16106-DBL-RD-WHI-EM)

Model	Faces	Letter Color	Housing	Options
16106	SGL Single Face DBL Double Face	RD Red GR Green	WHI White BLK Black	EM Emergency Backup Battery USA Assembled in USA SDT Self-Diagnostic Testing