

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

The specification grade Alcon Lighting Stanton Architectural LED Sign Light Fixture is designed to work outdoors. LED sign lighting provides practical and stylish light to exterior signs.



FEATURES

- Construction:** Extruded aluminum floodlight with cast aluminum adjustable swivels
- Lens:** High impact clear acrylic
- Internal Driver:** 120-277v 20/60Hz input
- Lumens:** Please see 2nd page for lumen chart
- Wiring:** Standard 120v Black, White and Ground 9" lead wires
- Finish:** Black Texture polyester powder coat is standard. Optional finishes are available.
- Life:** 50,000 Hours
- Warranty:** 3 Years Carefree for Parts & Components
(Labor Not Included)
- Listings:** CE, cETLus, IP44

Alcon Lighting 31022 Stanton Architectural LED Sign Light Fixture



ORDERING INFORMATION Example: (31022-2-27K-BK)

Model	Length # Panels Wattage	Color Temp	Finish	Mounting
31022	2 (24" 3 Panels 30 watts)	27K 2700K 30K 3000K 41K 4100K	BK Black <small>Standard</small> BZ Bronze WH White	P2 2 x Posts (24" - 48")
	3 (36" 4 Panels 40 watts)			P3 3 x Posts (72")
	4 (48" 6 Panels 60 watts)			P4 4 x Posts (96")
	6 (72" 9 Panels 90 watts)			
	8 (96" 12 Panels 120 watts)			
	2HI (24" 3 Panels 90 watts)			
	3HI (36" 4 Panels 120 watts)			
	4HI (48" 6 Panels 180 watts)			
	6HI (72" 9 Panels 270 watts)			
	8HI (96" 12 Panels 360 watts)			

LUMENS CHART

SKU	Color Temp	Lumens	SKU	Color Temp	Lumens
31022-2	2700K	3,900	31022-6	2700K	11,700
31022-2	3000K	4,752	31022-6	3000K	14,256
31022-2	4100K	4,770	31022-6	4100K	14,310
31022-2HI	2700K	8,940	31022-6HI	2700K	26,820
31022-2HI	3000K	11,901	31022-6HI	3000K	35,703
31022-2HI	4100K	14,400	31022-6HI	4100K	43,200
31022-3	2700K	5,200	31022-8	2700K	15,600
31022-3	3000K	6,336	31022-8	3000K	19,008
31022-3	4100K	6,360	31022-8	4100K	19,080
31022-3HI	2700K	11,920	31022-8HI	2700K	35,760
31022-3HI	3000K	15,868	31022-8HI	3000K	47,604
31022-3HI	4100K	19,200	31022-8HI	4100K	57,600
31022-4	2700K	7,800			
31022-4	3000K	9,504			
31022-4	4100K	9,540			
31022-4HI	2700K	17,880			
31022-4HI	3000K	23,802			
31022-4HI	4100K	28,800			

LINE DRAWINGS

