

SPECIFICATION SHEET

Project Name: _____ Type: ____ Quantity: ____

Straight Connector



Joins two track channels in a straight line. May be used as an electric feed point.



T-Bar End Feed



Power feed with T-bar installations where T-bar is directly above track. Supplied with1/2" knock outs.



Live End with Canopy




Power feed to track at end of channel. Covers outlet box. Comes with standard 1/2" knock out.



Outlet Adaptor



Convenient plug receptacle for standard US plug.



Floating Canopy Connector



Power feed canopy mounts to standard outlet box, anywhere along track channel.



Live End




Power feed to track at end of channel. Comes with standard 1/2" knock out.



Slope Ceiling Track Adaptor



Allows for H Type track heads to hang vertically from sloped ceiling.



End Cap



Cap for end of channel. Included in standard track channel lengths.



L-Connector



Joins two track channels in a perpendicular fashion. May be used as an electric feed point.

| | _ | |
|-----------|--------|-------|
| Model | Finish | |
| 13000-L-1 | WH | White |
| | вк | Black |

Pg.1/3



X-Connector



Joins four track channels in a perpendicular fashion. May be used as an electric feed point.



Pendant Adapter




Allows for chain-hung fixtures to be used with existing track lighting. Supports up to 25 lbs. 2.5 Amps Max.



T-Connector




Joins three track channels. May be used as an electric feed point.



Mini Connector




Joins two track channels end to end.



Conduit Connector



Allows for surface wiring with standard 1/2" conduit.



Flexible Connector




Joins two track channels at any angle (up to 85° vertically or horizontally). May be used as an electric feed point.



Cord and Plug Connector




Power feed with electric plug.



Conduit Continuation Kit



Allows for continuation of a run with conduit.



Outlet Box Cover



Covers recessed junction box opening to a track lighting system.






Pendant Assembly Kit



Mounts track from the ceiling with a maximum distance of 4 feet between other pendant assembly kits.



Aircraft Cable Suspension Kit



Suspends track from high ceiling applications with 1/4" – 20 threaded coupling. Supplied with T-Bar mounting clip, ceiling plate, aircraft cable and couplers.



Listings:

