SHOP NOW

Project Name: Type: Quantity:

Alcon Remy **11172** Linear Vaportite LED Light

FIXTURE SPECIFICATIONS

INTENDED USE

The linear, wet location-rated vaportite LED light can be used for either indoor or outdoor spaces. With a gasket enclosure, our linear ceiling canopy product comes in 2-ft, 4-ft and 8-ft standard lenghts and is ideal for commercial kitchens, garages and warehouses. Mounting options include stem, chain, swivel-stem and surface. This light is made in the United States of America.

FEATURES

Construction:
Fully gasket fiberglass upper body with cold-rolled steel white finish reflector.
Mounting: Stem, chain, swivel stem and surface mounting.
CRI: 80+
Input Voltage: 120/277V, 50/60Hz
Ambient Operating Temperature: -22°F (-30°C) ~ 122°F (50°C)
Listings: cULus, CSA, IP65 and IP67, NSF International certified, ARRA compliant, Suitable for damp / wet location, Made in the USA
Warranty: 5 Years Carefree for Parts & Components (Labor Not Included)

BRKT
Pendant Mounting Bracket for 1/2" stem

TP
Tamper-Proof Stainless Steel Cam-Action Latch

WLDL
Wet Location Day Light Motion Sensor

WLOS
Wet Location Occupancy Sensor

SPEC GRADE · DIMMABLE · IP65 · IP67 · NSF · c UL us · CSA · MADE IN USA

ORDERING INFORMATION Example: (11172-S-218-27K-DRS-010-N)

Model	Mounting	Length | Wattage | Lumens	Color Temp	Lens	LED Driver	Distribution	Options
11172	**S** Surface **P** Pendant	**218** 2' | 18W | 2272lm **220** 2' | 20W | 2460lm **227** 2' | 27W | 3215lm **236** 2' | 36W | 3969lm **422** 4' | 22W | 2425lm **436** 4' | 36W | 3969lm **445** 4' | 45W | 4723lm **456** 4' | 56W | 5854lm **472** 4' | 72W | 7363lm **4100** 4' | 100W | 10182lm **822** 8' | 72W | 7363lm **836** 8' | 88W | 8871lm **845** 8' | 112W | 11134lm	**27K** 2700K **30K** 3000K **35K** 3500K **40K** 4000K **50K** 5000K	**DRS** Shallow acrylic lens in crepe pattern. 15% DR **TA1F**[1] Tapered 100% Frosted High Impact Acrylic.	**010** Standard 0-10V 10% Dimming **ES566** eldoLED 0-10V SOLOdrive **BLS** Bi-Level Step 40/100% **BLSxx** Bi-Level Step xx/100% **TLS** Tri-Level Step 30/70/100% **TLSxxzz** Tri-Level Step xx/zz/100%	**N** Normal **W**[2] Wide	**EM8** 8W EM Battery Backup **EM15** 15W EM Battery Backup **EM20** 20W EM Battery Backup **WLOS** Wet Location Occupancy Sensor **SSL** Stainless Steel Latch **TP** Tamper-Proof Stainless Steel Cam-Action Latch **WLDL** Wet Location Day Light Motion Sensor

1 Not available for 2 Foot length options.
2 Wide Distribution only Available for 2 and 4 foot lengths

DIMENSIONS

2 Foot

4 Foot

8 Foot

[Tapered Lens]

Specifications: *Tapered*

Length: 25-7/8", 50", 98"

Width: 6-5/8"

Depth: 4-7/8"

[Shallow Lens]

Specifications: *Shallow*

Length: 24", 48"

Width: 6-5/8"

Depth: 5"

Normal Distribution

Wide Distribution

PHOTOMETRICS

11172-218

Illuminance at a Distance

	Center Beam FC	Beam Width	
1.7FT	272 FC	4.5 FT	5.4 FT
3.3FT	72.3 FC	8.7 FT	10.5 FT
5.0FT	31.5 FC	13.2 FT	15.9 FT
6.7FT	17.5 FC	17.7 FT	21.3 FT
8.3FT	11.4 FC	21.9 FT	26.4 FT
10.0FT	7.87 FC	26.4 FT	31.8 FT

- Vert. Spread: 105.8°
- Horiz. Spread: 115.6°

11172-228

Illuminance at a Distance

	Center Beam FC	Beam Width	
1.7FT	385 FC	4.5 FT	5.4 FT
3.3FT	102 FC	8.7 FT	10.5 FT
5.0FT	44.5 FC	13.2 FT	15.9 FT
6.7FT	24.8 FC	17.7 FT	21.3 FT
8.3FT	16.2 FC	21.9 FT	26.4 FT
10.0FT	11.1 FC	26.4 FT	31.8 FT

- Vert. Spread: 105.8°
- Horiz. Spread: 115.6°

11172-436

Illuminance at a Distance

	Center Beam FC	Beam Width	
1.7FT	476 FC	4.5 FT	5.4 FT
3.3FT	126 FC	8.7 FT	10.5 FT
5.0FT	55.0 FC	13.2 FT	15.9 FT
6.7FT	30.6 FC	17.7 FT	21.3 FT
8.3FT	20.0 FC	21.9 FT	26.4 FT
10.0FT	13.7 FC	26.4 FT	31.8 FT

- Vert. Spread: 105.8°
- Horiz. Spread: 115.6°

11172-456

Illuminance at a Distance

	Center Beam FC	Beam Width	
1.7FT	702 FC	4.5 FT	5.4 FT
3.3FT	186 FC	8.7 FT	10.5 FT
5.0FT	81.1 FC	13.2 FT	15.9 FT
6.7FT	45.2 FC	17.7 FT	21.3 FT
8.3FT	29.4 FC	21.9 FT	26.4 FT
10.0FT	20.3 FC	26.4 FT	31.8 FT

- Vert. Spread: 105.8°
- Horiz. Spread: 115.6°

11172-872

Illuminance at a Distance

	Center Beam FC	Beam Width	
1.7FT	883 FC	4.5 FT	5.4 FT
3.3FT	234 FC	8.7 FT	10.5 FT
5.0FT	102 FC	13.2 FT	15.9 FT
6.7FT	56.8 FC	17.7 FT	21.3 FT
8.3FT	37.0 FC	21.9 FT	26.4 FT
10.0FT	25.5 FC	26.4 FT	31.8 FT

- Vert. Spread: 105.8°
- Horiz. Spread: 115.6°

11172-8112

Illuminance at a Distance

	Center Beam FC	Beam Width	
1.7FT	1335 FC	4.5 FT	5.4 FT
3.3FT	354 FC	8.7 FT	10.5 FT
5.0FT	154 FC	13.2 FT	15.9 FT
6.7FT	85.9 FC	17.7 FT	21.3 FT
8.3FT	56.0 FC	21.9 FT	26.4 FT
10.0FT	38.6 FC	26.4 FT	31.8 FT

- Vert. Spread: 105.8°
- Horiz. Spread: 115.6°

COMPATIBLE DIMMERS

Manufacturer	Dimmer SKUs
LUTRON®	NTSTV-DV NFTV DVTV DVSCTV DVSTV QSGRJ-XP QSGRJ-XE QSGRJ-XE QSGR-XE RMJ-5T GRX-TVI
LEVITON®	IP710-DLZ IP710-LFZ
PHILIPS	SR1200ZTUNV