

SPECIFICATION SHEET

Shop Now

Project Name: Type:

INTENDED USE

Ideal for outdoor architectural lighting, this cube LED wall fixture features a durable, chip- and fade-resistant powder-coated finish. The 18-inch model includes a top cover lens for wet location rating. Perfect for residential and light commercial use, including porches, patios, garages, back entrances, and select indoor areas.

FEATURES

Construction: Heavy-duty aluminum and die-cast aluminum

wall bracket with durable powder coat finish

Color Temperature: 27/30/40/50K and Turtle Friendly Light Distribution: Direct Downlight and Direct/Indirect

options

Beam Spread: 25° and 40°

Wattage: 12.5W (static white) and 15W (turtle friendly) Lumens: 1200 lm (static white) and 450 lm (turtle friendly) Input Voltage: 120-277V (static white) and 120V (turtle

friendly) **CRI:** 80+

Life: 25,000 Hours

Warranty: 1 Year carefree for parts & components

(Labor not included)

Listings: cULus listed, suitable for wet locations













18-Inch



12-Inch

		Beam Angle	Lumens	Color Temp	
Static W		25/40°	1100 lm	2700K	
	- \4/1-:+-	25/40°	1100 lm	3000K	
	ic white	25/40°	1150 lm	4000K	
		25/40°	1200 lm	5000K	
Turtle	Friendly	40°	450 lm	630nm Amber	


ORDERING INFORMATION Example:


Model	Light Direction Size		Finish		Color Temp		Beam Spread	
11222	D DirectDI Direct / Indirect	12" 18"	WH BK BZ	White Black Bronze	27K 30K 40K 50K TF	2700K 3000K 4000K 5000K 630nm Turtle Friendly	25 ¹ 40	25° 40°

1 Not available with Turtle Friendly option.



LINE DRAWINGS & DIMENSIONS





LIGHT DISTRIBUTION



Direct/Indirect



Direct Downlight

TURTLE FRIENDLY WAVELENGTH CHART

