

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

The Pavo LED Architectural 2-Direction Wall Mount Light is a versatile low glare fixture that can be used indoor and outdoor in commercial or retail settings with dual reflectors that allow for direct and indirect lighting. The 2-Direction Pavo is used to accent and create dramatic effects while providing a great source of lighting.

FEATURES

Construction: Square one piece high grade aluminum extrusion with die cast aluminum top plate, tamper resistant

Light Engine: LED chip-on-board

Lens: Round one piece extruded aluminum with powder coat finish, clear, tempered glass and silicone O-ring

Reflector: Glare-free, one piece, heavy gauge aluminum

Mounting: Includes bracket for installation directly to a 4" octagonal electrical junction-box

Voltage: 120V (120-277 available for dimming)

Wattage: 30W

Lumen: 2 x 1000 lms



CRI: 84+

Life: L70 - 50,000 hours

Emergency: 90 minutes minimum

remote test switch, plate cover, junction box included

Listing: cETLus, cULus, Title 24, IP65, Suitable for wet location



ORDERING INFORMATION Example:

Model	Beam Spread (Down)	Beam Spread (Up)	Dimming	Color Temp	Finish	Options
11227-2D	WF60 60° Wide Flood	WF60 60° Wide Flood	ND ¹ Non-Dimming (120V)	17K ¹ 1700K	WH White	XEM External
	PE2 ¹ 2° Pencil	PE2 ¹ 2° Pencil	O10 0-10V Dimming (120V/277V)	20K ¹ 2000K	BK Black	Emergency
	NS10 ¹ 10° Narrow Spot	NS10 ¹ 10° Narrow Spot		27K 2700K	BR ¹ Bronze	Backup
	SP20 ¹ 20° Spot	SP20 ¹ 20° Spot		30K 3000K	SL ¹ Silver	Battery
	FL45 45° Flood	FL45 45° Flood		35K 3500K		
	WW Wall Wash	WW Wall Wash		40K 4000K		
	IV Type IV (forward throw)	IV Type IV (forward throw)		50K 5000K		
				56K ¹ 5600K		
				27C ¹ 2700K (97 CRI)		
				30C ¹ 3000K (97 CRI)		

¹ Special Order. Minimum lead time may apply.
Minimum Order Required (25).