

Project Name: \_\_\_\_\_ Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

### INTENDED USE

Featuring a half cylinder design, this tall outdoor wall sconce is suitable for wet locations such as stairwells, patios, garages, and as front door porch lights. Our wall sconce is available as a 120V–277V model that includes a daylight photocell.

### FEATURES

**Construction:** Aluminum Frame  
**Lens:** UV resistant, frosted  
**Beam Spread:** 120° beam angle  
**Color Temperature Switch:** 30/40/50K  
 Selectable switch  
**Voltage:** 120–277V  
**Driver:** TRIAC  
**CRI:** 80+  
**Life:** 50,000 Hours  
**Operating Temperature:** –40°F to 113°F  
**Listings:** cULus certified, Suitable for Wet Location, Energy Star listed  
**Warranty:** 5 years carefree for parts & components (Labor not included)

Bronze

Available in 10", 24" & 18"



Black

Available in all sizes



Satin Nickel

Available in all sizes



### ORDERING INFORMATION Example:

Model	Height   Wattage   Lumens	Finish	Options
11254	10 10 Inch   15W   1,361 lm	BR <sup>1</sup> Bronze	PC <sup>2</sup> Photocell
	18 18 Inch   20W   2,457 lm	SN Satin Nickel	
	24 24 Inch   25W   3,017 lm	BK Black	
	36 36 Inch   30W   3,268 lm		

<sup>1</sup> Not available in 36-Inch height

<sup>2</sup> Available only in 10-Inch height in bronze and satin nickel finish. Photocell makes the fixture non-dimmable.

## COLOR TEMPERATURE GUIDE

