


RISK OF FIRE AND ELECTRICAL SHOCK. FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY IN ACCORDANCE WITH NATIONAL, LOCAL BUILDING AND ELECTRICAL CODES. DISCONNECT POWER AT ELECTRICAL PANEL BEFORE SERVICING.

## 11259 INSTALLATION INSTRUCTIONS FOR: 3-Inch Outdoor Slim Flexible Linear LED Light Strip

## **Safety Precautions:**

- Read Carefully: Prior to installation or servicing, thoroughly read and understand all safety precautions and instructions. Failure to follow these guidelines may result in serious injury, electric shock, or property damage.
- Qualified Installation: It is strongly recommended that all wiring be performed by a licensed electrician. This fixture must be installed in compliance with all national and local electrical codes.
- Avoid Wet Conditions: Do not handle or attempt to energize the fixture with wet hands, or while standing
  on wet surfaces or in water. Do not install within 10 ft or less from the nearest edge of a pool, spa,
  fountain, or similar location
- Verify Power Source: Ensure the power source meets the fixture's requirements.



- 2. Align the spring clips to the mounting holes in the channel and place mounting channel to the surface. Use a level to make sure the channel is straight. Place a mounting bracket minimum every 8".
  - \* The number of brackets may vary depending on your pattern.
- 3. Secure channel to the surface by tightening all the provided screws; starting at the power input end. Make sure to keep a distance between the power input and channel.
  - \*If mounting to a non-wood surface, it is recommended to use proper hardware.
- 4. Secure the Architectural LED Wall Wash Track Light into place by carefully pushing the light strip onto the channel or mounting brackets.
  \*Please do not bend product beyond factory recommendation. (Refer to product spec sheet for factory bending limits.)
- 5. Connect the LED supply wires to the source wires. Match the polarity.



