




 RISK OF FIRE AND ELECTRICAL SHOCK. FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY IN ACCORDANCE WITH NATIONAL, LOCAL BUILDING AND ELECTRICAL CODES. DISCONNECT POWER AT ELECTRICAL PANEL BEFORE SERVICING.

MOUNTING LOCATION




Nominal Length	 12100-21 -33 (Flat and Regressed lens)			 12100-22 Width					
				12100-22 (Flat and Regressed lens)			12100-22 (Louver lens)		
	"A" Inch	"B" Inch	"C" Inch	"A" Inch	"B" Inch	"C" Inch	"A" Inch	"B" Inch	"C" Inch
2ft.	6.73"	4.07"	10.24"	6.73"	4.07"	10.24"	6.79"	4.07"	10.24"
3ft.	12.74"	4.07"	10.24"	12.74"	4.07"	10.24"	12.70"	4.07"	10.24"
4ft.	18.74"	4.07"	10.24"	18.74"	4.07"	10.24"	18.60"	4.07"	10.24"
8ft.	42.50"	4.07"	10.24"	42.50"	4.07"	10.24"	42.22"	4.07"	10.24"

RISK OF FIRE AND ELECTRICAL SHOCK. FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY IN ACCORDANCE WITH NATIONAL, LOCAL BUILDING AND ELECTRICAL CODES. DISCONNECT POWER AT ELECTRICAL PANEL BEFORE SERVICING.

IMPORTANT

1. Read all instructions.
2. Install in accordance with national and local electrical code regulations.
3. This product is intended to be installed and serviced by a qualified, licensed electrician.
4. Do not install in wet locations. For dry and damp use only.
5. Turn off electrical power before installing or servicing fixture in any way.
6. To reduce the risk of fire and overheating, make sure all connections are tight.
7. Under no circumstances can the lighting fixture be covered with heat insulation gasket or similar materials.
8. The maximum connection of each input line is 40FT (1200CM) in 120AC, 80FT (2400CM) in 230AC, and 100FT (3000CM) in 277AC.

ACCESSORY




WIRING

CORD / SUPPLY WIRING		LUMINAIRE
LINE	●	LINE- BLACK
GREEN	●	GROUND- GREEN
NEUTRAL	●	NEUTRAL- WHITE
DIM (+) VIOLET	●	VIOLET
DIM (-) PINK	●	PINK

Please isolate two dimming wires by P2 terminal individually if no need dimming; **MUST connect wires with corresponding colors as shown.**


INDEPENDENT INSTALLATION

1 Assemble Power Cord




Take off the end cap and LED module, thread the power cord out of the housing as shown.
Wiring and then remount LED module and end cap.

2 Install mounting point on wall




Nominal Length	12100-21 -33 Width (Flat and Regressed lens)			12100-22 (Flat and Regressed lens)			12100-22 (Louver lens)		
	"a"	"b"	"c"	"a"	"b"	"c"	"a"	"b"	"c"
	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet
2ft.	0.34'	0.22'	0.85'	0.34'	0.22'	0.85'	0.34'	0.25'	0.85'
3ft.	0.34'	0.72'	0.85'	0.34'	0.72'	0.85'	0.34'	0.72'	0.85'
4ft.	0.34'	1.22'	0.85'	0.34'	1.22'	0.85'	0.34'	1.12'	0.85'
8ft.	0.34'	3.20'	0.85'	0.34'	3.20'	0.85'	0.34'	3.18'	0.85'

3 Install plate and bracket




- 3-1: Insert Anchor "G" into hole and fix the wall mounting bracket "K" with screw "I".
- 3-2: Mount the square cover plate "D" onto J-box with screw "H", then plaster it.

4 Wiring




- 4-1: Plug in AC wires, dimming wires and ground wire into the male quick connector (5 holes) "E" according to label instructions.
- 4-2: Plug in the male and female connector together, hide all wires into the junction box.

5 Mounting



Match the hole position of the fixture and "wall mounting bracket", and mount the fixture onto wall with screw "J".

6 Complete



⚠ RISK OF FIRE AND ELECTRICAL SHOCK. FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY IN ACCORDANCE WITH NATIONAL, LOCAL BUILDING AND ELECTRICAL CODES. DISCONNECT POWER AT ELECTRICAL PANEL BEFORE SERVICING.

ACCESSORY



Run Joiner




Silicone Seal

Note: Silicone Seal is used to seal seams that may appear at both ends of luminaires when multiple connections.


BEFORE CONNECTING

Disassemble luminaires




MULTIPLE LUMINAIRES CONNECTION

1 Install mounting point on wall




2 Install plate and bracket from SoR to EoR



Nominal Length	12100-21 -33 (Flat and Regressed lens)				12100-22 (Flat and Regressed lens)				12100-22 (Louver lens)			
	"a"	"b"	"c"	"d"	"a"	"b"	"c"	"d"	"a"	"b"	"c"	"d"
	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet	Feet
2ft.	0.34'	0.22'	0.85'	1.11'	0.34'	0.22'	0.85'	1.11'	0.34'	0.25'	0.85'	1.12'
3ft.	0.34'	0.72'	0.85'	2.11'	0.34'	0.72'	0.85'	2.11'	0.34'	0.72'	0.85'	2.10'
4ft.	0.34'	1.22'	0.85'	3.11'	0.34'	1.22'	0.85'	3.11'	0.34'	1.12'	0.85'	3.08'
8ft.	0.34'	3.20'	0.85'	7.07'	0.34'	3.20'	0.85'	7.07'	0.34'	3.18'	0.85'	7.02'


3 Wiring – SoR



3-1: Plug in AC wires, dimming wires and ground wire into the male quick connector (5 holes) "E" according to label instructions.


3-2: Plug in the male and female connector together, hide all wires into the junction box.

4 Mounting



Match the hole position of the fixture and "wall mounting bracket", and mount the fixture onto wall with screw "J".

5 Repeat install and join steps – MoR to EoR



6 Complete

