

Project Name: \_\_\_\_\_ Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

### INTENDED USE

The 1-Inch Linear LED Tube Pendant Downlight offers a refined lighting solution for offices, hospitality settings, galleries, studios, and contemporary residential spaces. Designed for precision and performance, this slim-profile fixture provides high-CRI illumination with multiple color temperature options and length configurations. Its anodized aluminum housing supports efficient thermal management, while a frosted lens ensures smooth, glare-free light distribution—ideal for continuous-run installations in architecturally driven interiors.

### FEATURES

**Construction:** Anodized aluminum for excellent thermal management

**Lens:** Frosted for uniform light distribution and reduced glare transmissivity, designed to slide into the housing

**Finish:** Silver

**CRI:** 98+

**Input Voltage:** 24V DC

**Wattage:** 10 watt per ft

**Lumen Output:** 937 lumens per ft



**External Dimming Driver:** 0-10V, MLV, ELV, and TRIAC

**Operating Temperature:** -40°F (-40°C) to 140°F (+60°C)

**Life:** 50,000 Hrs

**Listings:** cULus Listed and California Title 24 JA8 Compliant for energy-efficient, high-performance lighting

**Warranty:** 5 years carefree for parts & components (Labor not included)



Alcon Lighting 12117 1-Inch Linear LED Tube Pendant Downlight




### ORDERING INFORMATION Example:

Model	Length	Color Temp	Accessories
12117	4	27K	5PWH
	8	30K	5PBK
	CR <sup>1</sup>	35K	2NPWH
		40K	2NPBK
			5NPWH
			5NPBK


<sup>1</sup> Specify in foot

## ACCESORIES

### End Caps (Included)




5" Power Feed  
(Black and White)




5PBK, 5PWH

2" Non-powered Feed  
(Black and White)



2NPBK, 2NPWH


5" Non-powered Feed  
(Black and White)



5NPBK, 5NPWH

## EXTERNAL DIMMING DRIVER

Driver	Dimensions
4N1-30 W-24V	6.50" x 3.72" x 1.57"
4N1-60 W-24V	7.40" x 3.72" x 1.57"
4N1-96 W-24V	8.66" x 3.72" x 1.57"
4N1-150 W-24V	10.24" x 4.13" x 1.77"
4N1-2 00W-24V	10.24" x 4.13" x 1.77"
4N1-300 W-24V	10.94" x 4.33" x 1.77"



	ALCON LIGHTING	LUTRON	LEVITON®
0-10 V	<a href="#">2100</a> <a href="#">2101</a> <a href="#">2102</a>	Diva DTVV	IP-710-DL

## COLOR TEMPERATURE GUIDE

