

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

Offering industrial, commercial-grade LED lighting in 2-foot, 4-foot and 8-foot standard lengths. Design can be customized, color can be changed and the canopy can be power-coated to match your desired finish. This corrosion-resistant product's built with formed and welded 22-gauge steel. The linear light, available in surface or pendant mount, includes a snap-in, glare-free frosted lens.

FEATURES

Construction: Die-formed and welded 22-gauge cold rolled steel

Lens: Glare-free snap-in frosted acrylic for even distribution

Voltage: 120-277V


CRI: 83

Dimming: 0-10V, ELV

Life: 50,000 Hours

Warranty: 1 Year carefree for parts & components (labor not included)

Listings: cETLus Listed, IC-rated for damp and dry locations, Assembled in the US



ORDERING INFORMATION Example: (12122-S-2-D14-30K-010-WH-LV-EM)

Model	Mounting	Wattage Lumens	Shape	Single Run	Specify Length: 2', 4' or 8'	Color Temp	Dimming Driver	Finish	Pendant Mounting	CRI	Options
				Cont. Run	Specify Run Length in Feet 2' increments						
12122	P Pendant S Surface	Wattage & Lumens per Foot D7 7 watts 875 lumens D10 10 watts 1250 lumens	S Single Run CR Continuous Run			30K 3000K 35K 3500K 40K 4000K 50K 5000K	010 Standard 5-Wire 0-10V 120-277V (100%-10%) ELV-TRI 3-Wire ELV/2-Wire TRIAC 120V (100%-1%)	Standard WH White BK Black SL Silver Premium ¹ RD Red BL Blue GR Green OR Orange SB Satin Brass	AC4 4 Foot Aircraft Cable AC12 12 Foot Aircraft Cable ST2 2 Foot Stem Mount (Blank) Not Required	8 Standard 80+ CRI 9 90+CRI	EM14 ² 14W Internal Emergency Backup Battery EM20 20W Remote Emergency Backup Battery OS Occupancy Sensor w/ Daylight Harvesting VS Vacancy Sensor

¹ Additional Lead Time will be Applied
² Not available for 2FT length