# **SPECIFICATION SHEET**

**Shop Now** 

Project Name: \_\_\_\_\_ Type: \_\_\_\_ Quantity: \_\_\_\_

## **FIXTURE SPECIFICATIONS**

### **INTENDED USE**

The specification grade decorative Architectural LED Ring Light delivers continuous clean lines and clear circle light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish hanging lights designs offer excellent direct lighting, indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The ring light ring chandelier is available in multiple lengths and several finishes.

### **FEATURES**

Pendant: 8' Adjustable Aircraft Cable/Power Cord Included

(Custom length available, Consult MFG)

Construction: Extruded aluminum outer housing Adjustable power cord and

AC cables with push button grippers standard

Lens: White frosted acrylic diffuser

Reflector: Glare-free, one piece, heavy gauge aluminum


**Mounting:** All standard J-boxes **Voltage:** 120/277V, 50/60 Hz. **Driver:** 0-10V (100-1%)

**CRI:** 90

S – Standard

Emergency: 90 minutes minimum, Remote install only





### ORDERING INFORMATION Example: (12280-3-30K-WH-WH-S)

Model	Size   Wattage   Lumens	Color Temp	Finish	Mounting	Options
12280	<b>3</b> 3 ft   75 Watts   5438 Lumens	<b>30K</b> 3000K	<b>WH</b> White	<b>S</b> Standard	<b>EM</b> 7W Emergency Battery Pack
	4 ft   99 Watts   7248 Lumens	<b>35K</b> 3500K	<b>SL</b> Silver	<b>SR</b> Standard Remote	XX Custom AC Cable/Power Cord (25' Max)
	5 ft   124 Watts   9062 Lumens 6	<b>40K</b> 4000K	<b>BK</b> Black	<b>M</b> Medial	<b>DMX</b> DMX Controller
	6 ft   149 Watts   10875 Lumens <b>8</b>	RGBW RGB + 3500K		<b>MR</b> Medial Remote	
	8 ft   209 Watts   15116 Lumens				













**Cross Section** 



# STATIC WHITE COMPATIBLE DIMMERS

	LIGHTING	<b>%LUTRON</b>	<b>LEVITON</b> <sub>®</sub>
	2100	Diva DVTV	IP-710-DL
0-10 V	<u>2101</u>		
	<u>2102</u>		

