

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

Our 2, 3, and 4-foot antimicrobial, surface-mounted or wall-mounted linear LED light, made in America, mounts on the wall for various healthcare applications, such as utility rooms, corridors, stairwells, closets, nail salons, barber shops, dormitory and general work areas. With optional, integral ultrasonic motion sensors, this product, suitable for damp locations, is coated with antimicrobial paint to prevent rust and corrosion.

FEATURES

Lens: Frosted acrylic glass

Voltage: 120-277V, 50/60 Hz


Finish: White antimicrobial finish

Operating Temperature: -4°F (-20°C) ~ 122°F (50°C)

Life: 54,000 hours

Warranty: Standard 5 years carefree for parts & components (labor not included)

Listing: UL listed, Made in USA, ARRA compliant, Wet Location, EM options are CEC compliant, Made in the USA



-UOS
Ultrasonic Occupancy Sensors
(Optional)

ORDERING INFORMATION Example: (12523-22L-30K-80-010)

Model	Length Wattage Lumen	Color Temp	CRI	Dimming	Warranty	Options
12522	22L 2 Foot 22 Watts 3080 lms	27K¹ 2700K	80 80+ CRI	010 0-10V 10%-100%	Blank <small>Standard</small> 5 Year Warranty	EM5 5W EM Battery Backup
	27L 2 Foot 27 Watts 3780 lms	30K 3000K	90 90+ CRI	BLS Bi-Level Step Dimming 50%/100%	W7 7 Year Warranty	EM8 8W EM Battery Backup
	28L 3 Foot 28 Watts 3920 lms	35K 3500K		BLSXX Bi-Level Step Dimming Replace X with Percentage from 10%-90%	W10 10 Year Warranty	EM16 16W EM Battery Backup
	42L 3 Foot 42 Watts 5880 lms	40K 4000K		TLS Tri-Level Step Dimming 30%/70%/100%		EM25 25W EM Battery Backup
	36L 4 Foot 36 Watts 5040 lms	50K 5000K		TLSXX Tri-Level Step Dimming Replace X and X with Percentages from 10%-90%		PO Power Outlet with Ground
	44L 4 Foot 44 Watts 6160 lms					UOS Ultrasonic Occupancy Sensor with Bi-level Step-Dimming
	50L 4 Foot 50 Watts 7000 lms					GTD Bodine Generator Transfer Device

¹ Only compatible with 90+ CRI option