

SPECIFICATION SHEET

Project Name: Quantity: Type:

INTENDED USE

The specification grade 13306 LED Adjustable Track Light delivers direct track lighting to commercial, hospitality and residential interior ceiling track lighting applications. Architecturally styled LED track lights feature small, unobtrusive size and are highly adjustable. Our modern LED track light fixture designs offer excellent illumination, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and

PRODUCT FAMILY

PRODUCT FA	PRODUCT FAMILY						
13000-TC	Track Channel						
13000-LC	Linear Connector						
13000-OA	Outlet Adapter						
13000-SC	Slope Ceiling Track Adapter						
13000-TB 13000-FC 13000-EC 13000-LC 13000-LE	T-Bar End Feed Floating Canopy Connector End Cap Live End with Canopy Live End						
13000-L	L-Connector						
13000-T	T-Connector						
13000-X	X Connector						
13000-MC	Mini Connector						
13000-CP	Cord and Plug Connector						
13000-PA	Pendant Adapter Conduit						
13000-CC	Connector Conduit						
13000-CK	Continuation Kit						



Construction: Solid die-cast aluminum

Adjustability: 100° Adjustable Track head with 355° rotation

Wattage: 12.5W Lumens: 700L

Installation: H-Track is standard; all tracks have adjustable adapters for use with

single or two-circuit tracks. J-Style or L-Style is optional.


CRI: 80+

LED Life: 50,000 Hours Dimming: TRIAC and ELV

Warranty: 5 Years Carefree for Parts & Components (Labor Not Included)

Listings: cULus, RoHS Compliant

















ORDERING INFORMATION Example: (13306-27-BK-H-SP-120)

Model	Color Temp	Finish	Track	Optics	Voltage
13306	27 2700K30 3000K40 4000K	BK Black WH White	HStandard H - Style J J - Style L L - Style	SP 19° Spot FL 30° Flood WF 45° Wide Flood	120 120V 277 277V