

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

The Illusione 4-Inch architectural LED trimless recessed light fixture is designed for lasting durability and beauty while providing quality and energy efficient lighting for low to medium ceilings. The Illusione is an ideal solution for clear and bright lighting in retail, hospitality, commercial, and high-end residential settings.

FEATURES

Construction: Heat-dissipating, die-cast aluminum

Lumens: 800/1000/1500/2000/2500 lm

Wattage: 14/20/24/28W

Color Temperature: 27/30/35/40/50K and Warm Dim (3100K-2000K)

Mounting: Two tensioned steel spring clips securely attach the luminaire to the ceiling, fitting into the included trimless mud ring. Supports ceiling thicknesses up to 3/4"

Dimming Driver: 0-10V, ELV, TRIAC

Voltage: 120-277V (0-10V Dim), 120V (TRIAC, ELV Dim)

Operating Temperature: 32°F ~ 104°F (0°C ~ 40°C)

CRI: 90+

Life: 50,000 hours L70

Warranty: 5 Years carefree for parts & components (Labor not included)

Listings: cULus suitable for damp and wet locations, RoHS, Energy Star, California Title 24 JA8-2022



ORDERING INFORMATION Example:

Model	Shape	Beam Spread	Housing	Wattage Lumens	Color Temp	Finish	Options
14074	SF¹⁶ Square Fixed RF Round Fixed RA^{8,11} Round Adjustable RS^{7,9} Round Adjustable Slot	(Blank)¹³ Field selectable 60 60° Frosted 73 73° Frosted TIR (Premium)¹² 10° 10° 22 22° 26 26°	IC IC Air-Tight CH Chicago Plenum	(Blank) Not Required 8 14W 800 lm 10⁴ 14W 1000 lm 15¹ 20W 1500 lm 20¹ 24W 2000 lm 25¹ 28W 2500 lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K¹⁰ 5000K WD Warm Dimming (3000K-2000K)	WH White OW Off-White BK Black SH Satin Haze BZ Bronze BB² Brushed Brass WB⁵ White Reflector / Brushed Brass Head WS⁵ White Reflector / Satin Haze Head OS⁵ Off-White Reflector / Satin Haze Head OB⁸ Off-White Reflector / Black Head	HEX Hex Cell Louver TF³ Trim Flange XEM⁶ External Emergency Battery

¹ Not available with 60° and 73° Frosted Lens.

² Not available with Round Fixed.

³ Flange Accessory matches fixture finish.

Available only with Round Fixed and Round Adjustable Slot.

⁴ Not available with Warm Dimming.

⁵ Available only with Round Adjustable.

⁶ Not available with 14W | 800/1000 lm.

⁷ Available only with 14W | 800/1000 lm.

⁸ Available only with 12W | 850lm.

⁹ Available only for Damp Locations.

¹⁰ 5000K 800 lm LED modules available while supplies last.


¹¹ Not available with 28W | 2500 lm.

¹² Precise and sharper beam angle, minimal light spill and glare.


¹³ Round 23°, 38°, 55° and Square 40°, 51°, 71°.

LINE DRAWINGS & DIMENSIONS


Square Fixed




Square Mud Ring




IC / CH - Housing




Round Adjustable Slot




Round Mud Ring





Square Trimless



Round Trimless



Round Trimmed




ACCESSORIES

Frosted Lens



Available in 60° and 73° beam spreads, softens light output to deliver more diffuse, glare-free illumination. Ideal for ambient lighting in residential, hospitality, or commercial spaces.

Hex Cell Louver



Designed to subtly reduce brightness at the fixture aperture, controls glare and minimizes visual distraction by 20%, enhancing visual comfort and lighting control in refined spaces.

Suction Cup for Removal



Facilitates easy removal of the trimless downlight or reflector from the ceiling post-installation. Especially useful for ongoing maintenance or optical adjustments in inaccessible or finished ceilings.

Removal Tool



Included with Square Fixed fixture, simplifies the safe extraction of the trimless reflector from the ceiling after installation. Ideal for routine maintenance and optical component replacement.

Trim Flange



Converts a trimless recessed fixture into a flanged version. No mud ring or drywall finishing needed. Ideal for retrofits and quick installs, available in multiple finishes to match housing and architectural design.

AVAILABLE FINISHES



Black



Bronze



Black Head
Off-White Reflector




Satin Haze Head
Off-White Reflector



Brushed Brass



Satin Haze



Brushed Brass Head
White Reflector



Satin Haze Head
White Reflector



Off-White



White

LUMINOUS EFFICACY

Shape	Lumen Package	Beam Angles
Square Fixed	1500 – 2500 lm	40° Spot, 51° Narrow Flood, 71° Flood
Round Fixed	800 / 1000 lm	23° Spot, 38° Narrow Flood, 55° Flood
	1500 – 2500 lm	Spot, Narrow Flood, Flood
Round Adjustable	800 / 1000 lm	23° Spot, 38° Narrow Flood, 55° Flood
	1500 / 2000 lm	30° Spot, 45° Narrow Flood, 65° Flood
Round Adjustable Slot	800 / 1000 lm	23° Spot, 38° Narrow Flood, 55° Flood

COLOR TEMPERATURE GUIDE

2700K

WARM WHITE

friendly
personal
intimate

HOMES
LIBRARIES
RESTAURANTS

✓

3000K

SOFT WHITE GLOW

soft
warm
pleasing

HOMES
HOTEL ROOMS
LOBBIES
RETAIL STORES

✓

3500K

NEUTRAL GLOW

sociable
inviting
non-threatening

EXECUTIVE OFFICES
RECEPTION AREAS
SUPERMARKETS

✓

4000K

COOL WHITE GLOW

neat
clean
efficient

OFFICES
CLASSROOMS
MASS MERCHANTISERS
SHOWROOMS

✓

5000K

DAYLIGHT GLOW

bright
cool
alert

GRAPHICS INDUSTRY
HOSPITALS
GALLERIES
BEAUTY SALONS

✓