

## SPECIFICATION SHEET

Project Name: \_\_\_\_\_ Type: \_\_\_\_ Quantity: \_\_\_\_

#### **INTENDED USE**

The 4-inch architectural LED trimless recessed fixtu e delivers efficien , high-quality lighting for low to medium ceilings. Ideal for retail displays, hospitality settings, commercial interiors, and upscale residential spaces, it offers clean, modern illumination. Its regressed cone refle tor minimizes glare and adjusts up to 35° for precise light control.

#### **FEATURES**

Construction: Heat-dissipating, die-cast aluminum

Lumens: 800/1000/1500/2000/2500 lm

Wattage: 14/20/24/28W

Color Temperature: 27/30/35/40/50K and Warm Dim

(3100K-2000K)

**Mounting:** Two tensioned steel spring clips securely attach the luminaire to the ceiling, fitting in o the included trimless mud ring. Supports ceiling thicknesses

up to 3/4"

Dimming Driver: 0-10V, ELV, TRIAC

Voltage: 120–277V (0–10V Dim), 120V (TRIAC, ELV Dim) Operating Temperature:  $32^{\circ}F \sim 104^{\circ}F$  ( $0^{\circ}C \sim 40^{\circ}C$ )

**CRI**: 90+

Life: 50,000 hours L70

Warranty: 5 Years carefree for parts & components

(Labor not included)

15 Only available with Comfort Dim

Listings: cULus suitable for damp and wet locations,

RoHS, California Title 24 JA8-2022



























Square Mud Ring



Round Mud Ring

# ORDERING INFORMA TION Example:


							L
Model	Shape	Beam Spread	Housing	Wattage   Lumens	Color Temp	Finish	Options
Square Fixed RF Round Fixed RA®***  ROUND			(Blank) 88d. 12W-14W   800-850 Im <sup>15</sup> 10 14W   1000 Im 15' 20W   1500 Im 20' 24W   2000 Im 25' 28W   2500 Im	27K 2770K 30K 300K 35SK 3500K 40K 4000K 50K <sup>®</sup> 5000K	WH White OW Off-White BK Black SH Satin Haze BZ Bronze BB <sup>2</sup> Brushed Brass WB <sup>4</sup> White Refle tor / Brushed Brass Head WS <sup>4</sup> White Refle tor / Satin Haze Head OS <sup>4</sup> Off-White Refle tor / Satin Haze Head OB <sup>4</sup> Off-White Refle tor / Black Head	HEX Hex Cell Louver TF® Trim Flange XEM® External Emergency Battery	

Rev: 08/14/25




# LINE DRAWINGS & DIMENSIONS

# Square Fixed




## •




Square Mud Ring

IC / CH - Housing




Round Adjustable Slot




**Round Mud Ring** 







**Square Trimless** 



**Round Trimless** 



# **Round Trimmed**





## **ACCESSORIES**

#### **Frosted Lens**



Available in 60° and 73° beam spreads, softens light output to deliver more diffuse, glare-free illumination. Ideal for ambient lighting in residential, hospitality, or commercial spaces.

#### Removal Tool



Included with Square Fixed fixtu e, simplifies the sa e extraction of the trimless refle tor from the ceiling after installation. Ideal for routine maintenance and optical component replacement.

## Hex Cell Louver



Designed to subtly reduce brightness at the fixtu e aperture, controls glare and minimizes visual distraction by 20%, enhancing visual comfort and lighting control in refined spaces

### Trim Flange



Converts a trimless recessed fixtu e into a flan ed version. No mud ring or drywall finishing needed. Ideal or retrofits and quick in talls, available in multiple finishes o match housing and architectural design.

# **AVAILABLE FINISHES**



Black



Bronze



Black Head Off-White Refle tor



Satin Haze Head Off-White Refle tor



**Brushed Brass** 



Satin Haze



Brushed Brass Head White Refle tor



Satin Haze Head White Refle tor



Off-White



White



# **LUMINOUS EFFIC ACY**

Shape	Lumen Package	Beam Angles		
Square Fixed	1500 – 2500 lm	40° Spot, 51° Narrow Flood, 71° Flood		
Down d Fire d	1000 lm	25° Spot, 38° Narrow Flood, 60° Flood		
Round Fixed	1500 – 2500 lm	42° Spot, 54° Narrow Flood, 66° Flood		
Day and Adia at all la	1000 lm	23° Spot, 38° Narrow Flood, 55° Flood		
Round Adjustable	1500 / 2000 lm	30° Spot, 45° Narrow Flood, 65° Flood		
Round Adjustable Slot	1000 lm	23° Spot, 38° Narrow Flood, 55° Flood		

