

SPECIFICATION SHEET

Shop Now

4250/3000/2250 Im

6192/4692/3744 lm

Dualast Names	т	O
Project Name:	 Type: _	Quantity:

INTENDED USE

Our Troffer Light, available in 2'x2', and 2'x4' sizes, is designed for grid installations. Engineered with optimized LED optics and electronics, it ensures uniform, high-quality illumination while maximizing energy efficiency. Ideal for commercial and institutional spaces such as offices, schools, and retail environments, it delivers reliable performance and modern lighting solutions.

FEATURES

Construction: Solid die-formed, cold-rolled steel with a interior highly reflective, powder-coated finish for durability and optimal light distribution

Finish: Baked white matte paint, applied after fabrication **Lens:** Diffuser ensures uniform, glare-free illumination with no pixelation

Mounting: Recessed installation in a T-bar grid. LED modules and drivers are accessible directly from the fixture for easy maintenance—no plenum access required

Color Temperature: 35/40/50K Selectable switch

Voltage: 120-277V Driver: 0-10V CRI: 82+

Operating Temperature: -4°F-131°F

PowerFactor: > 0.95

TotalHarmonicDistortion: 20%

Warranty: 5 years carefree for Parts & Components (Labor

Not Included)

Listings: UL/cUL listed with all components UL approved. UL Class 2 compliant. Power supply includes SCP, OTP, and OVP protection, meeting FCC Part 15 Class B and UL8750 Class 2 standards. DLC Premium listed















2' x 2'

2' x 4'

ORDERING INFORMATION Example:

Model	Size	Options	
14079	22 2'x2' 24 2'x4'	EM8 8W, 700 Im Emergency Back-up Battery EM15 15W, 1400 Im Emergency Back-up Battery EM20 2000 Im Emergency Back-up Battery OS Microwave Motion & Daylight Harvesting Sensor SC Smart Control System CT Cold Temperature Driver (-40°F-131°F)	




34/24/18W


48/34/26W




LINE DRAWINGS



2' x 4'







COMPATIBLE DIMMERS

	LIGHTING	%LUTRON	LEVIT <mark>ON</mark> 。
	<u>2100</u>	Diva DVTV	IP-710-DL
0-10 V	<u>2101</u>		
	2102		

