

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

With a frosted round lens and die-cast aluminum heat sink housing, the Darwin 15230 is ideal for warehouse, gymnasium and other mid to high-ceiling applications where high output LED lighting is desired.

FEATURES

Construction: Die cast aluminum heat sink housing. Spun .063 aluminum reflector.

Lens: Frosted round lens, safe for food service applications

CRI: 90+


LED: Nichia Corp.

Driver: 0–10V 5-wire 1% dimming.

Input Voltage: 120/277V, 50/60Hz

Emergency Back Up: 10W optional emergency back up battery available.

Listings: cUL listed for damp locations, Made in the USA



ORDERING INFORMATION Example:

Model	Exterior Finish	Interior Finish	Color Temp	Wattage Lumens	Mounting	Canopy Color	Cord Color	Options
15230	BK Black	WH White	30K 3000K	5L 32 Watts 5000 lms	Surface Driver S-AC96 96" Adjustable Aircraft Cable S-AACXX Custom Adjustable Aircraft Cable (Replace XX with Length in Inches)	BK Black	BK Black	EM10 10W Emergency Back up Battery (90 minutes)
	WH White	GD Gold	35K 3500K	10L 64 Watts 10000 lms		SL Silver	G Gray	
	SL Silver	AN Anodized	40K 4000K	15L 96 Watts 15000 lms		WH White	WH White	
					Remote Driver R-AC96 96" Adjustable Aircraft Cable R-ACXX Custom Adjustable Aircraft Cable (Replace XX with Length in Inches)			
					ST24 24" Stem			
					ST36 36" Stem			
					ST48 48" Stem			
					STXX Custom Stem (Replace XX with Length in Inches)			

			
0-10 V	2100 2101 2102	Diva DTVT	IP-710-DL

COLOR TEMPERATURE GUIDE

