


Project Name: \_\_\_\_\_ Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

### INTENDED USE

The Architectural Perimeter LED Cove Recessed Light is designed to enhance interior spaces by delivering a seamless wash of light where walls meet ceilings. Ideal for open offices, private workspaces, lobbies, corridors, and reception areas, it defines architectural perimeters with subtle accent lighting that adds depth and visual clarity. Engineered for clean integration and easy installation, it creates a refined transition from wall to ceiling while expanding the perceived size of narrow or enclosed areas.

### FEATURES

**Construction:** Extruded aluminum housing with powder coat finish  
**Mounting:** Supports threaded rod installation to the ceiling (rod provided by others) or wall mounting using the included hook and bracket assembly  
**Ceiling Type:** Compatible with both Hard Drywall and T-Grid  
**Lens:** Diffuser  
**Light Distribution:** 100% down  
**Lumens:** 500lm/ft, 750lm/ft, and 1000lm/ft  
**Wattage:** 50/75/100% selectable switch  
**Color Temperature:** 30/35/40K selectable switch  
**Voltage:** 110-277V  
**Driver:** 0-10V dims to 10%  
**CRI:** 80+  
**Life:** 50,000 Hours  
**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)  
**Warranty:** 5 Years carefree for parts & components (Labor not included)  
**Listings:** cULus, listed for damp locations




### ORDERING INFORMATION Example:

Model	Regressed Depth	Width	Length			Finish		Options	
15233	2 2"	22 2.3"	SR <sup>1</sup>	Single Run	SR = 2', 3', 4' or 8'	WH	White	IT	1' Illuminated Telescoping Section
	4 4"	33 3.8"	CR <sup>2</sup>	Continuous Run	CR = Length	BK	Black	IC	Inside Corner
	6 6"							OC	Outside Corner


<sup>1</sup> Quickship 8' length available only with 3.8" width option.

<sup>2</sup> Supports runs up to 40 feet on 120VAC and up to 100 feet on 277VAC connections.

LINE DRAWINGS & DIMENSIONS



OPTIONAL PARTS



PERFORMANCE

Width	Length	Wattage Selectable	Efficacy	Lumen Output	Color Temperature
2.3"	2'	20/15/10W	Up to 1000 lm/ft	Up to 2000 lm	3000/3500/4000K
	3'	30/23/15W		Up to 3000 lm	
	4'	40/30/20W		Up to 4000 lm	
	8'	80/60/40W		Up to 8000 lm	
3.8"	2'	20/15/10W	Up to 1100 lm/ft	Up to 2200 lm	
	3'	30/23/15W		Up to 3300 lm	
	4'	40/30/20W		Up to 4400 lm	
	8'	80/60/40W		Up to 8800 lm	

**Note:** Specific total lumen outputs per fixture length at maximum wattage and 4000K with White Finish. May vary  $\pm$  5% based on different Color Temperature and Wattage.

COMPATIBLE DIMMERS

			
0-10 V	<a href="#">2100</a> <a href="#">2101</a> <a href="#">2102</a>	Diva DDTV	IP-710-DL

COLOR TEMPERATURE GUIDE



**2700K**  
WARM  
WHITE

friendly  
personal  
intimate

HOMES  
LIBRARIES  
RESTAURANTS

X



**3000K**  
SOFT WHITE  
GLOW

soft  
warm  
pleasing

HOMES  
HOTEL ROOMS  
LOBBIES  
RETAIL STORES

✓



**3500K**  
NEUTRAL  
GLOW

sociable  
inviting  
non-threatening

EXECUTIVE OFFICES  
RECEPTION AREAS  
SUPERMARKETS

✓



**4000K**  
COOL WHITE  
GLOW

neat  
clean  
efficient

OFFICES  
CLASSROOMS  
MASS MERCHANDISERS  
SHOWROOMS

✓



**5000K**  
DAYLIGHT  
GLOW

bright  
cool  
alert

GRAPHICS INDUSTRY  
HOSPITALS  
GALLERIES  
BEAUTY SALONS

X