

SPECIFICATION SHEET



Project Name: Type: Quantity:

INTENDED USE

The Alcon Lighting 15295 Micro LED Recessed Rectangular Downlight delivers precise accent, task, and general illumination in a discreet architectural form. Designed for versatility, it enhances residential interiors such as kitchens, living rooms, hallways, and home theaters, while also performing seamlessly in commercial offices, conference rooms, retail boutiques, showrooms, hospitality spaces, hotels, restaurants, reception areas, lounges, museums, and galleries. Its minimalist profile and glarecontrolled output make it an ideal choice for design-driven environments.

FEATURES

Dimensions: L 5.79" × W 1.77" × H 1.93" (Cutout: 5.39" × 1.42") Construction: Die-cast aluminum housing with integrated 5-head LED module. External driver in junction box

Mounting: Recessed, no housing required

Light Distribution: Narrow to medium flood with low-glare

black reflector

Beam Spread: 15°, 30°, 45°

Color Temperature: 27/30/40/50K

Lumens: 650-700 lm Efficacy: 65 lm/W

Wattage: 10W (5 × 2W LED heads)

Driver: TRIAC (120V)

Voltage: 120-277V AC, 50/60 Hz

Power Factor: >0.9

CRI: 90+


Life: 50,000 Hours

Warranty: 5 Years carefree for parts & components

(Labor not included)


Listings: cETLus listed for Damp locations.


IC-Rated & Air Tight





















ORDERING INFORMATION Example:

					ı		I
M	lodel	Finish ¹		Color Temp Lumens			Beam Spread
15	5295	WH BK	White Black	27K 30K 40K 50K	2700K 650 lm 3000K 660 lm 4000K 680 lm 5000K 700 lm	15 30 45	15° Narrow Spot 30° Medium Flood 45° Wide Flood

1 Inner reflector is black



COMPATIBLE DIMMERS

	LUT	RON
--	-----	-----



TRIAC

CTCL-153P DVCL-153P S-600P SLV-600P CN-600P 6674 6672

COLOR TEMPERATURE GUIDE 2700K 3000K 3500K 4000K 5000K **WARM SOFT WHITE** NEUTRAL **COOL WHITE** personal inviting intimate non-threatening pleasing efficient CLASSROOMS MASS MERCHANDISERS SHOWROOMS