



FIXTURE SPECIFICATIONS

INTENDED USE

The **Atlas Architectural LED Dual Head Emergency Unit** features bright illumination with a fire and impact resistant housing for durability. The Atlas is an ideal option for outdoor applications where emergency lighting is needed.

FEATURES

Construction: Die-Cast Aluminum Housing
Sealed and Gasketed
Mounting: Surface via Easy Connect Back Plate
Suitable for Wall Mount
Electrical: Charge Rate/Power "ON" LED Indicator Light and Push-to-Test Switch for Mandated Code Compliance Testing
Battery: Fully Automatic Solid-State, Two Rate Charger
Wiring: Field-Selectable Wiring Allows for "AC" Operation
Lamp: 6W (2 LEDs x 3W) per Unit
Lens: Prismatic Polycarbonate Mirror-Bright Reflector
Voltage: 120/277 VAC
Wattage: 6W
Self-Diagnostic Testing: Continuously Diagnoses Units' Performance and Test Systems
Sensor: Photocell
Warranty: 5 Years
Battery Pro-Rated for 5 Years
Listings: Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local, and State Codes
UL Listed for Wet Location 32° F (0°C) - 122°F (50°C)



ORDERING INFORMATION Example: (16102-BK-CW)

Model	Finish	Options
16102	BK Black WH White BR Dark Bronze NI Nickel	CW¹ Cold Weather

¹Internal Self-Regulating Heater for Extreme Cold Temperatures (-20° C - 50°C)