



FIXTURE SPECIFICATIONS

INTENDED USE

The **EMU II Architectural LED Dual Head Emergency Unit** features bright illumination with a fire and impact resistant housing for durability. The EMU II is an ideal option for outdoor applications where emergency lighting is needed.

FEATURES

Construction: Injection-Molded, Engineering Grade, 5VA Flame Retardant, High-Impact Resistant Thermoplastic
Two Adjustable LED Lamp Heads
Electrical: Charge Rate/Power "ON" LED Indicator Light and Push-to-Test Switch for Mandated Code Compliance Testing
Battery: 3.6V Long life, Maintenance-Free Rechargeable Ni-Cad Fully Automatic Solid-State, Two Rate Charger. LVD (Low Voltage Disconnect) prevents battery from deep discharge.
Mounting: Suitable for Wall or Surface Mount
 Surface Mount via Easy Connect Back Plate
Lens: High Performance Chrome-Plated Metalized Reflector with Plastic Lens
Voltage: 120/277 VAC
Wattage: 1W (8 LEDs x 0.125 watt) per Head
Self-Diagnostic Testing: Continuously Diagnoses Units' Performance and Test Systems
Warranty: 5 Years
 Battery Pro-Rated for 5 Years
Listings: Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local, and State Codes
 Tested to Meet Requirements of CSA C22.2 No. 141.10
 Standard for Emergency Lighting Equipment
 UL Listed for Damp Location 32° F (0°C) - 122°F (50°C)



ORDERING INFORMATION Example: (16104-BK-SPV)

Model	Finish	Options
16104	BK Black WH White	WG-1 Steel Wire Guard (13.5" x 15" x 6") BGR-1 Polycarbonate Vandal Shield Guard (7.5" x 18" x 5") SPV 208/220/240 Volt, 50/60Hz