

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

Our Alcon 31029 is a specification grade fixture featuring a sealed aluminum extrusion with lens for outdoor wet applications. 31029 is a durable fixture suitable for parking structures, commercial or retail outdoor areas, for sign and walkway lighting.

FEATURES

Construction: Powder-coated white aluminum extrusion with white interior and cast-aluminum end plates. The diffuser/lens is a smooth clear acrylic.

Mounting: Mounts on to conduit (Supplied by others, please see installation instructions). Wet location for downlight only. 3/4" Hub. Fixture rotates up to 90°. Instructions for joining two units together can be found on page 4 of the installation instructions.



Voltage: 120/277 voltage (ELV/TRIAC @ 120V only).

CRI: 80+

Life: 50,000 Hours L70

Warranty: 1 Years Carefree for Parts & Components (Labor Not Included)

Listing: cETLus. Wet location for downlight only.



ORDERING INFORMATION Example:

Model	Length	Wattage Lumen	Color Temp	Finish	Driver
31029	4 4 Foot	48 48 Watts 5900 Lum	30K 3000K	WH <small>Standard</small> White	O10 0-10V Dimming 120-277V
		57 57 Watts 6500 Lum	35K 3500K	BK Black	
	8 8 Foot	96 96 Watts 11800 Lum	40K 4000K	SL Silver	ELV/TRI ELV/Triac Dimming 120V only
		114 114 Watts 13000 Lum	50K 5000K	BR Bronze	

COLOR TEMPERATURE GUIDE

				
2700K	3000K	3500K	4000K	5000K
WARM WHITE	SOFT WHITE GLOW	NEUTRAL GLOW	COOL WHITE GLOW	DAYLIGHT GLOW
friendly personal intimate	soft warm pleasing	sociable inviting non-threatening	neat clean efficient	bright cool alert
HOMES LIBRARIES RESTAURANTS	HOMES HOTEL ROOMS LOBBIES RETAIL STORES	EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS	OFFICES CLASSROOMS MASS MERCHANDISERS SHOWROOMS	GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS
X	✓	✓	✓	✓

