

INSTALLATION INSTRUCTIONS FOR WELL LIGHT LINE VOLTAGE LIGHT FIXTURE SERIES 9044

This Product Must Be Installed in Accordance with the Applicable Installation Code by a Person Familiar with the Construction and Operation of the Product and the Hazards Involved

Installation recommended to be done by a professional electrician and must be in accordance with local codes of the National Electrical Code (NEC)

TOOLS REQUIRED FOR INSTALLATION:

Wire Strippers, Flathead Screwdriver, Philips Screwdriver

WARNING: TO REDUCE THE RISK OF FIRE OR INJURY TO PERSONS:

1. To prevent electrical shock, disconnect power supply before servicing.
2. Do not touch lens, guard or enclosures. Allow fixture to cool down before servicing.
3. Do not operate fixture with missing or damaged parts.

INSTALLATION

1. To prevent electrical shock, disconnect before installation or service.
2. Remove lens cover screws.
3. Remove reflector and socket bracket to expose the rear housing.
4. Pull wires through housing.
5. Connect wires according to color code (**White on White, Black on Black**).
6. Replace reflector and socket bracket.
7. Install lamp with correct wattage and type of lamp marked on fixture label.
8. Re-install lens cover.
9. Reconnect power after servicing.

LAMP INSTALLATION/ REPLACEMENT:

CAUTION: DO NOT EXCEED MAXIMUM WATTAGE MARKED ON FIXTURE LABEL.

1. To prevent electrical shock, disconnect power supply before replacing lamp.
2. Remove shroud to expose lamp.
3. Replace lamp with correct wattage and type of lamp marked on fixture label.

NOTE: DO NOT touch Halogen Lamp with bare hands. Always use the plastic bag (if available) or soft cloth when handling the lamp.

4. Re-install shroud.
5. Reconnect power.