

Project Name:	Type:	Quantity:

INTENDED USE

Delivering modern style and reliable illumination for pathways, parks, and commercial landscapes, our Flat Top LED Bollard features a precision-engineered cone reflector that provides uniform, glare-controlled lighting, enhancing visibility while maintaining visual comfort. Ideal for both safety and aesthetic enhancement, this hardwired LED bollard provides long-lasting, energy-efficient performance with minimal maintenance.

FEATURES

Construction: Corrosion Resistant Aluminum Lens: Impact-resistant polycarbonate lens

Beam Spread: 360 Degrees

Hardwired Wattage Selectable Switch: Selectable from

7W/14W/22W

Color Temperature Switch: Selectable from

30K/40K/50K

CRI: 70+

Operating Temperature: -40°F ~ +104°F

Life: 70,000 Hours

Warranty: 7 Years carefree for parts & components

(Labor not included)

Listings: UL Listed, IP65, Wet Location

Wattage | Lumens

Wattage	Lumens
8 Watts	1040 Lumens
13 Watts	1690 Lumens
18 Watts	2340 Lumens
25 Watts	3250 Lumens















ORDERING INFORMATION Example: 9083-BZ-30-GFCI

Model Finish Height Options Emergency Back-up Battery 9083 ΒZ **Bronze** 14 Inch EM² 14 Photocell BK Black 30 30 Inch OS² Microwave Sensor SL Silver Metalic MS² WH White Hammer Beige Hammer BE CC Custom Finish (See Page 3)



LINE DRAWINGS & DETAILS





