



READ AND FOLLOW ALL INSTRUCTIONS BEFORE ASSEMBLY, INSTALLATION, OR USE OF THIS FIXTURE. FAILURE TO COMPLY WITH THE INSTRUCTIONS IN THE MANUAL MAY INCREASE THE RISK OF DAMAGE OR INJURY AND WILL VOID THE WARRANTY.

Thank you for choosing our lighting fixture. To ensure the best experience, please take a moment to carefully read and follow all instructions before installation and use. Doing so will help guarantee proper performance, safety, and durability, while allowing you to make the most of this product's design and functionality.

WARNING: THE LAMP BECOMES HOT DURING OPERATION.

1. Use caution when operating the fixture, as it heats up rapidly during use. Always allow the lamp to cool completely before attempting to touch or move it.
2. Never touch the lens, guard, or housing while the lamp is operating or still hot. Contact with hot surfaces may cause burns.
3. Keep the fixture clear of flammable materials and surroundings to avoid the risk of fire.
4. This electrical product must be installed by a qualified electrician or trained professional who is familiar with local codes and standards.
5. Always disconnect or turn off power at the main circuit breaker before beginning installation or maintenance.

WARRANTY

Thank you for choosing Alcon Lighting. **This fixture is backed by a 5-year warranty covering parts and components from the date of purchase** (labor not included; warranty does not extend from the date of installation).

- Keep your sales receipt or proof of purchase, as it will be required for any warranty claim.
- The warranty does not cover damage caused by incorrect installation, improper use, accidents, modifications, or neglect.
- Ignoring the directions in this manual may cause injury or product failure and will void the warranty.



READ AND FOLLOW ALL INSTRUCTIONS BEFORE ASSEMBLY, INSTALLATION, OR USE OF THIS FIXTURE. FAILURE TO COMPLY WITH THE INSTRUCTIONS IN THE MANUAL MAY INCREASE THE RISK OF DAMAGE OR INJURY AND WILL VOID THE WARRANTY.

INSTALLATION INSTRUCTION

To achieve optimal performance and ensure safety, this fixture must be used only with a **low-voltage landscape transformer**. The transformer reduces standard line voltage (120V) down to 12V, making it safe for outdoor landscape lighting applications.

Follow these steps carefully:

Power Off: Turn off electricity at the main switch or breaker before installation begins.

Positioning: Hold the mounting plate against the wall, deck, or step at the desired height and orientation. Use a level to confirm alignment.

Marking Holes: With a pencil or marker, mark the screw hole locations through the pre-drilled slots in the plate.

Drilling Pilot Holes: Choose a drill bit slightly smaller than the screws provided. Drill shallow pilot holes at the marked locations to avoid cracking or weakening the surface.

Concrete / Deck Installation (if applicable)

For concrete: Before pouring, create conduit raceways using 1-inch dowels and PVC pipe. Remove dowels once cured.

For decks: Cut an opening sized for the fixture and align it with the prepared mounting surface.

WIRING THE FIXTURE

For safe, waterproof connections, we recommend **waterproof wire nuts (sold separately)**.

1. Strip approximately ¾ inch of insulation from each wire
2. Align the stripped ends of the fixture and supply wires
3. Insert into a wire nut and twist clockwise until secure
4. Wrap with electrical tape for added protection
5. Tug wires gently to confirm a solid connection.
- 6.

CAUTION: All wiring must meet local electrical codes and ordinances.

ADJUSTING THE FIXTURE

Wattage (Brightness Control)


1. Insert the included flat screwdriver into the power adjustment slot.
2. Turn clockwise or counterclockwise to select between 1W, 2W, 3W, or 4W brightness levels.

Color Temperature (CCT Control)

1. Locate the arrow switch on the fixture.
2. Toggle back and forth from positions 1–4 three times.

Each sequence changes the CCT to:

- 3000K – Warm White
- 4000K – Neutral White
- 5000K – Cool White



Repeat until the desired CCT is reached.



READ AND FOLLOW ALL INSTRUCTIONS BEFORE ASSEMBLY, INSTALLATION, OR USE OF THIS FIXTURE. FAILURE TO COMPLY WITH THE INSTRUCTIONS IN THE MANUAL MAY INCREASE THE RISK OF DAMAGE OR INJURY AND WILL VOID THE WARRANTY.

INSTALLATION INSTRUCTION

MOUNTING THE FIXTURE

Pass mounting screws through the housing and lens.

Align the fixture with drilled pilot holes or dowels.
Tighten screws until secure, avoiding over-tightening.

Confirm that the fixture is flush, snug, and level.

Avoid harsh chemicals or abrasives that could damage the finish.

Periodically inspect wiring connections for security and integrity.

Proper maintenance will extend fixture performance and lifespan.



FINAL STEPS

Turn power back on at the breaker or switch.

Observe the fixture to ensure proper illumination and alignment.

Enjoy the enhanced visibility, safety, and atmosphere provided by your Alcon Lighting step light.

MAINTENANCE AND CARE

Regularly clean the fixture with a dry or slightly damp cloth to remove dust, dirt, or debris.

CAUTION:

Fixture(s) must be installed in accordance with all local codes and ordinances.
Do not instal within 10 feet of a poll, spa or fountain.