

SPECIFICATION SHEET

Shop Now

Project Name:

Type: Quantity:

INTENDEDUSE

The specification grade VE Lighting 12031 Hamilton Architectural LED Linear Pendant Mount Direct Down Light Fixture furnishes both clean lines and clarity to commercial LED office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

FEATURES

SPFC

GRADE

Construction: Anodized Aluminum Lumens: 4400lms Wattage: 40W Uplight, 20W Downlight. 60W Total. CRI: 80+ Voltage: 120-277VAC 50/60Hz Dimming: O-10V Dimmable Color Temperature: 35/40/50K selectable switch Operating Temperature: -13°F ~ 104°F (-25°C ~ 40°C) Life: 50,000 Hours Power Factor: >0.95 Listings: UL Listed, LM79 Rated, Assembled in the US Warranty: 5 Years Carefree for Parts & Components (Labor Not Included)


Comes standard with 6 Foot Adjustable Aircraft Cable

5

YEAR

ARRAN





ORDERING INFORMATION Example: (12030-SJTW100)

IMMABLE

Model		Option
12030	Blank SJTW100	6-Foot Aircraft Suspension Cable 100 Foot Reel of 5-Conductor 18 AWG Power Cable 8 Watt
	EM8	Internal Emergency Back-Up Battery
