

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade Basic Architectural LED Recessed Troffer fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

AVAILABLE SIZES

2x2 | W 11.75" x L 24" x H 4"

2x4 | W 23.75" x L 24" x H 4"

1x4 | W 11.75" x L 48" x H 4"

FEATURES

Construction: Die-formed and embossed code 22 gauge steel housing Access plate to simplify installation

Finish: High reflectance baked white enamel

Lens: Clear 0.10 thick A12 Acrylic

Voltage: 120-277V (50/60 Hz) Constant Current

Support: Recessed Inverted T-Bar Ceilings. Grid Mount.

Life: 50,000 Hrs

CRI: 80+

Operating Temperature: -4°F~122°F

Lamp Included

Listings: UL Listed

Warranty: 5 Years Carefree for Parts & Components
(Labor Not Included)



ORDERING INFORMATION Example: (14115-22-30K-ND)

Model	Size	Wattage Lumens	Color Temperature	Dimming	Options
14115	22 2x2	<small>2x2 Options</small>	30K	ND	EM
		24 24 Watts 2700lms	3000K	Non-Dimming	Emergency
		28 28 Watts 3200lms	35K	DM10	Backup Battery
		35 35 Watts 3900lms	3500K	5-Wire	
	24 2x4	<small>2x4 Options</small>	40K	0-10V Dimming	
		35 35 Watts 4600lms	4000K	(100%-10%)	
		40 40 Watts 5300 lms	50K	DM1	
	14 1x4	<small>1x4 Options</small>	5000K	5-Wire	
		35 35 Watts 4300 lms		0-10V Dimming	
		48 48 Watts 5800 lms		(100%-1%)	

Alcon Lighting 14115 Basic Architectural LED Recessed Troffer Direct Down Light

FIXTURE DIMENSIONS

