

Wire Leads (Leads Extend 6" Beyond Mounting Knuckle).

Utilizes any PAR36 or AR111 Lamp, up to 75 Watts.

Integral Class H 120V to 12V Transformer Potted and Sealed.

Completely Sealed Optical Compartment, Clear Tempered Glass Lens, Factory Sealed.

Cushioned Lamp Seat to Eliminate Lamp Vibration.

Tamperproof Design, Utilizes Three Hex Head Set Screws.

ACV (Patented) Valve System.

Polyester Powdercoat Finishes Standard. (Specify)

CATALOG NUMBER LOGIC

EXAMPLE: – BLP – WH - 429 - 11 -

Series: -Lamp Type: ·

26

- By Others

-4414PAR36(18W),

50°/25° Flood - 36 PAR36/CAP/VNSP(36W), 5° V.N. Spot - 36 PAR36/CAP/NSP(36W), 13° N. Spot

27 PAR36/CAP/WFL(36W), 30° W. Flood 28 - 36 PAR36/Q/VNSP(50W), 29 - 50 5° V.N. Spot

30 PAR36/NSP(50W), - 50

- 50 - 35 - 35 PAR36/WFL(50W). 31 35 AR111/4/VNSP(35W),

36 AR111/8/SP(35W), 37 - 35 AR111/25/FL(35W)

- 50 38 AR111/4/VNSP(50W), - 50 39

AR111/8/SP(50W), - 50 40 AR111/25/FL(50W). 41 - 75 AR111/8/SP(75W).

- 75 - 75 42 AR111/25/FL(75W) AR111/45/WFL(75W), 43

8° Spot 25° Flood 45° W. Flood

8° N. Spot

4° V.N. Spot

4° V.N. Spot

8° Spot

8° Spot

25° Flood

25° Flood

30° W. Flood

Finish .-

<u>r IIII8II</u> .		
Powdercoat	Satin	Wrinkle
Bronze	BZP	BZW
Black	BLP	BLW
White (Gloss)	WHP	WHW
Aluminum	SAP	
Verde		VER

Lens Type:-

- Clear (Standard)

- Spread 13 - Rectilinear

Shielding: -

- Honeycomb Baffle

Cap Style:

A - 45°

B - 90° C - Flush



WHITNEY SERIES[™]

B-K LIGHTING, INC.

DRAWING NUMBER SUB-1134-08