

For Use With 120V.  
No Transformer Required.

STYLE A

Clear Lens  
(Standard)

Optional Lens or Shielding  
(Up to Two can be Specified  
w/3 3/8" MOL PAR20 Lamp)

Locking  
O-Ring  
Compression  
Knuckle

9 3/8"

STYLE B

7"

1"

STYLE C

3" Dia.

6"

1/2" Pipe Thread

1 5/8"

1/2"

CATALOG NUMBER LOGIC

EXAMPLE: MC - 49 - VER - 9 - 11 - B

Series: \_\_\_\_\_

Lamp Type: \_\_\_\_\_

0 - By Others  
47 - 50 PAR20/H/NSP(50W), 9° N. Spot  
49 - 50 PAR20/H/NFL(50W), 30° N. Flood

Finish: \_\_\_\_\_

Powdercoat	Satin	Wrinkle
Bronze	BZP	BZW
Black	BLP	BLW
White (Gloss)	WHP	WHW
Aluminum	SAP	---
Verde	---	VER

Lens Type: \_\_\_\_\_

9 - Clear (Standard)  
10 - Spread  
13 - Rectilinear

Shielding: \_\_\_\_\_

11 - Honeycomb Baffle

Cap Style: \_\_\_\_\_

A - 45°  
B - 90°  
C - Flush

**Features:**

All Precision Machined Aluminum Construction.

Locking O-Ring Compression Knuckle (THE L.O.C.K.™) Allows Vertical to Horizontal Aiming and Provides Integral, Sealed Wireway.

Med. Base Lampholder With 250°C, 18 Ga. Wire Leads (Leads Extend 6" Beyond Mounting Knuckle).

Utilizes any PAR20 Lamp, up to 50 Watts.

Completely Sealed Optical Compartment, Clear Tempered Glass Lens, Factory Sealed.

Tamperproof Design, Utilizes a Single, Flush Mtd. Hex Screw.

Polyester Powdercoat Finishes Standard. (Specify)



<b>McKINLEY SERIES™</b>		
8/03	<b>B-K LIGHTING, INC.</b>	DRAWING NUMBER SUB-1131-03