

LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



**110 BSH Series
Vandal Resistant**



**Four Panel 110BSH45LED
Shown Above**

- Ceiling Mounted Indoor or Outdoor Under Canopy Vandal Resistant Fixture, 15" Square
- Designed for Use in Schools, Hospitals, Commercial, and Industrial Buildings
- UL Damp Location
- Easy Install, Enclosed Conduit Pan With Knockouts Standard for Alternative Wiring Access, Hinged Ballast Access, Heavy 18 Gauge Stamped Steel Pan With Durable White Powder Coat Finish
- Easy Access Hinged Lens Assembly, Standard Low Profile High Impact Acrylic Prismatic Diffuser, Vandal Resistant Prismatic Polycarbonate Diffuser Upon Request (X)
- **Distributed Array Board** by Osram Sylvania consists of 48 low-power LEDs in a precise layout that enables thermal self-management; eliminating the need for a supplemental heat sink. Board produces an even, diffused light that reduces the need for multiple optical layers and maximizes optical efficiency.
- **4000K** Standard, 3500K and 3000K Available, 80+CRI
- **Osram Sylvania, Optronic OT50W 4x320 mA, Electronic LED Power Supply** 120-277 VAC, 500-210 mA, 50/60 Hz, Dimmable from 10%-100%, Class 2 Power Supply, Complies with FCC47 CFG Part 15, Class B, No PCBs, Power Factor >0.90, THD < 20%, Sound Rated A, Thermally Protected

Independently Tested & Certified to IES LM-79 and IES LM-80, ANSI C78 377-2008

Model	Watts	Rated Average Panel/Driver Life	Lumens	Osram LED Power Supply/Driver	H	W1	W2
110BSH22LED	27	55,000 Hrs.	2160	Electronic (120-277V)	5.25"	15"	15"
110BSH34LED	40	55,000 Hrs.	3160	Electronic (120-277V)	5.25"	15"	15"
110BSH45LED	52	55,000 Hrs.	4230	Electronic (120-277V)	5.25"	15"	15"

**Vertically Integrated Manufacturer
Made In USA**