



architectural

Fixture Type .....

Job Name .....

# Light Bell

Ceiling Mounted Suspended Luminaire

### Description

Ceiling mounted suspended luminaire for indoor applications. It's high efficiency, latest generation LED light source and low-loss technical thermoplastic diffuser makes it a great replacement for typical high-bay fixture. The reflector is supplied separately and is available in spun aluminum or transparent glass. Power supply source integrated into luminaire light source.




### Lamps

- LED: Vossloh Schwabe 46.8W, 2700K, 90CRI, 3332lm To be ordered separately.
- LED: Vossloh Schwabe 55.3W, 3000K, 82CRI, 5481lm To be ordered separately.


### Construction

- Aluminum or transparent glass reflector
- Pendant cable extends to a maximum of 13.2 feet.



### Electrical

- Integral (120V- 50/60Hz) power supply.



### Notes

- Listings: UL Listed, IP20
- For complete order information, please order reflector, light source and canopy separately.

### Reflector

- Different color finishes for exterior and interior surfaces.
- Reflector sits on light source and is easily replaceable.

### Photometrics

For current IES files please visit [flosusa.com](http://flosusa.com)

### Warranty

2 years from date of sale



### How to Specify

Product Series	Ceiling Appearance	Lamps	Reflector Finish	Accessories	Voltage
Light Bell	Suspended	07.9641.14.90= LED, 27K, 90CRI 07.9642.14.90= LED, 3K, 82CRI	07.9630.AP= Polished Aluminum- exterior Anodized Aluminum- interior 07.9630.70= White- exterior Anodized Aluminum- interior 07.9630.AN= Black- exterior Gold- interior 07.9630.MM= Brown- exterior Gold- interior 07.9630.76= Transparent Glass	F0556020 F0556020= Power supply rose for indoor. IP20	120V 277V Univ

### Ordering information notes

F L O S . U S A  
110 York Street  
Brooklyn, NY 11201  
(718).875.3472

For more information contact your representative or go to [FlosUSA.com](http://FlosUSA.com).  
©2014 Specifications and dimensions subject to change without notice.



**Lamps**



07.9641.14.90=  
LED, 27K, 90CRI, 46.8W

07.9642.14.90=  
LED, 3K, 82CRI, 55.3W

**Drivers**



60.8584 (07.9641)=  
Xitium 50W 0-1.0A 36V 0-10V INT



60.8315 (07.9642)=  
Lightech LED 60W 0-10V

**Power supply rose**



F0556020=  
Power supply rose  
for indoor. IP20

**Reflector Finishes**

07.9630.AP=  
Polished Aluminum- exterior  
Anodized Aluminum- interior



07.9630.70=  
White- exterior  
Anodized Aluminum- interior



07.9630.AN=  
Black- exterior  
Gold- interior



07.9630.MM=  
Brown- exterior  
Gold- interior



07.9630.76=  
Transparent Glass

