

	Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
A15															
†	5.7 Watt	Med.	80753	A15/6WW/LED	Warm White Dimmable	120	2700	82	270	-	40000	1/6	-	4.13"	25
A16															
†	5 Watt	Med.	80694	A16/5WW/LED	Warm White Dimmable	120	2700	82	220	-	40000	1/10	-	3.50"	25
A19															
⊗	5 Watt	Med.	80020	A19/5WW/LED	Warm White Dimmable	120	3000	82	260	-	25000	1/6	-	4.25"	25
⊗	8 Watt	Med.	80022	A19/8WW/LED	Warm White Dimmable	120	3000	82	450	-	25000	1/6	-	4.25"	40
	8.3 Watt	Med.	80754	A19/8WW/LED2	Warm White Dimmable	120	2700	82	400	-	40000	1/6	-	4.33"	40
A22															
^ †	13 Watt	Med.	80696	A22/13WW/LED	Warm White Dimmable	120	2700	82	520	-	40000	1/10	-	5.40"	40
B11															
⊗	2 Watt	E12	80014	B11/2WW/LED	Warm White	120	3000	82	65	-	40000	1/10	-	3.94"	15
BR30															
⊗	15 Watt	Med.	80778	BR30/15WW/FL/LED	Warm White Dimmable	120	3000	82	750	-	40000	1/6	-	5.28"	65
C7															
	0.96	Cand.	80510	C7CL/FC/LED	Clear Faceted	120	-	-	-	-	60000	10/200	-	1.30"	7
†	0.96	Cand.	80502	C7BLU/LED	Blue Smooth	120	-	-	-	-	60000	10/200	-	1.30"	7
	0.96	Cand.	80508	C7BLU/FC/LED	Blue Faceted	120	-	-	-	-	60000	10/200	-	1.30"	7
†	0.96	Cand.	80503	C7GRN/LED	Green Smooth	120	-	-	-	-	60000	10/200	-	1.30"	7
	0.96	Cand.	80509	C7GRN/FC/LED	Green Faceted	120	-	-	-	-	60000	10/200	-	1.30"	7
†	0.96	Cand.	80500	C7RED/LED	Red Smooth	120	-	-	-	-	60000	10/200	-	1.30"	7
	0.96	Cand.	80506	C7RED/FC/LED	Red Faceted	120	-	-	-	-	60000	10/200	-	1.30"	7
†	0.96	Cand.	80505	C7RG/LED	Red/Green Smooth	120	-	-	-	-	60000	10/200	-	1.30"	7
†	0.96	Cand.	80501	C7YEL/LED	Yellow Smooth	120	-	-	-	-	60000	10/200	-	1.30"	7
	0.96	Cand.	80507	C7YEL/FC/LED	Yellow Faceted	120	-	-	-	-	60000	10/200	-	1.30"	7
C9															
	0.96	Int.	80515	C9CL/FC/LED	Clear Faceted	120	-	-	-	-	60000	10/200	-	1.60"	7
	0.96	Int.	80513	C9BLU/FC/LED	Blue Faceted	120	-	-	-	-	60000	10/200	-	1.60"	7
	0.96	Int.	80514	C9GRN/FC/LED	Green Faceted	120	-	-	-	-	60000	10/200	-	1.60"	7
	0.96	Int.	80511	C9RED/FC/LED	Red Faceted	120	-	-	-	-	60000	10/200	-	1.60"	7
	0.96	Int.	80512	C9YEL/FC/LED	Yellow Faceted	120	-	-	-	-	60000	10/200	-	1.60"	7
G25															
⊗	8 Watt	Med.	80018	G25/8WW/LED	Warm White Dimmable	120	3000	82	430	-	35000	1/6	-	4.25"	40
JC10															
	1.5 Watt	G4	80693	JC10/1WW/LED	Warm White	10-18	3000	82	120	-	20000	1/40	-	1.81"	10
⊗	1.5 Watt	G4	80776	JC10/1WW/LED2	Warm White, IP65 Rated	10-18	3000	82	100	-	40000	1/10	-	1.75"	10
	1.5 Watt	BA15s	80692	JC10/1WW/BA15S/LED	Warm White	10-18	3000	82	120	-	20000	1/40	-	2.01"	10
JC20															
	2.4 Watt	G4	80690	JC20/2WW/LED	Warm White	10-18	3000	82	200	-	20000	1/40	-	1.81"	20
	2.4 Watt	BA15s	80691	JC20/2WW/BA15S/LED	Warm White	10-18	3000	82	200	-	20000	1/40	-	2.01"	20
⊗	2.5 Watt	G4	80774	JC20/2WW/LED2	Warm White, IP65 Rated	10-18	3000	82	140	-	40000	1/10	-	1.75"	20
⊗	2.5 Watt	BA15s	80775	JC20/2WW/BA15S/LED2	Warm White, IP65 Rated	10-18	3000	82	140	-	40000	1/10	-	2.25"	20
MR11															
†	2 Watt	G4	80604	MR11/2NW40/LED	Natural White Dimmable	8-16	5000	72	80	140	40000	1/10	40°	1.39"	15
	2.2 Watt	GU4	80703	MR11/2NW/FL/LED	Natural White Dimmable	10-18	5000	72	150	420	40000	1/10	30°	1.42"	15
	2.2 Watt	GU4	80705	MR11/2WW/FL/LED	Warm White Dimmable	10-18	2700	82	110	330	40000	1/10	30°	1.42"	15
	2.2 Watt	GU4	80704	MR11/2WW/NFL/LED	Warm White Dimmable	10-18	2700	82	110	860	40000	1/10	18°	1.42"	15
MR16															
⊗	3 Watt	GU5.3	80000	MR16/3WW/FL/LED2	Warm White	12	3000	82	150	360	40000	1/10	38°	1.97"	10
	3.3 Watt	GU5.3	80707	MR16/3NW/FL/LED	Natural White Dimmable	10-18	5000	72	180	420	40000	1/10	34°	2.20"	10
	3.3 Watt	GU5.3	80709	MR16/3WW/FL/LED	Warm White Dimmable	10-18	2700	82	150	380	40000	1/10	34°	2.20"	10

⊗ NEW ITEM!

† Available until inventory is depleted. Contact your Halco account representative for substitute.

^ Base down operation only.

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
MR16 cont'd														
3.3 Watt	GU5.3	80706	MR16/3NW/SP/LED	Natural White Dimmable	10-18	5000	72	180	1890	40000	1/10	13°	2.20"	10
3.3 Watt	GU5.3	80708	MR16/3WW/SP/LED	Warm White Dimmable	10-18	2700	82	150	1730	40000	1/10	13°	2.20"	10
3.5 Watt	GU10	80742	MR16/4NW/FL/GU10/LED	Natural White Dimmable	120	5000	72	190	490	40000	1/10	29°	2.17"	20
3.5 Watt	GU10	80743	MR16/4WW/FL/GU10/LED	Warm White Dimmable	120	2700	82	140	370	40000	1/10	30°	2.17"	20
4 Watt	GU10	80744	MR16/3M4NW/FL/GU10/LED	Natural White Dimmable	120	5000	72	300	640	40000	1/10	40°	2.17"	35
4 Watt	GU10	80745	MR16/3M4WW/FL/GU10/LED	Warm White Dimmable	120	2700	82	250	510	40000	1/10	40°	2.17"	35
4 Watt	GU5.3	80728	MR16/5RGB/FL/LED	Color Changing Red, Green, Blue	10-18	-	-	-	-	40000	1/10	31°	2.17"	NA
		80649	RGB/REMOTE	Remote Control for Color Changing MR16 lamp										
4.5 Watt	GU5.3	80712	MR16/3M4NW/FL/LED	Natural White Dimmable	10-18	5000	72	250	780	40000	1/10	35°	2.20"	20
4.5 Watt	GU5.3	80702	MR16/3M4WW/FL/LED	Warm White Dimmable	10-18	2700	82	200	560	40000	1/10	34°	2.20"	20
4.5 Watt	GU5.3	80711	MR16/3M4NW/NFL/LED	Natural White Dimmable	10-18	5000	72	250	1560	40000	1/10	20°	2.20"	20
4.5 Watt	GU5.3	80714	MR16/3M4WW/NFL/LED	Warm White Dimmable	10-18	2700	82	200	1100	40000	1/10	23°	2.20"	20
4.5 Watt	GU5.3	80710	MR16/3M4NW/SP/LED	Natural White Dimmable	10-18	5000	72	250	2500	40000	1/10	12°	2.20"	20
4.5 Watt	GU5.3	80713	MR16/3M4WW/SP/LED	Warm White Dimmable	10-18	2700	82	200	1900	40000	1/10	11°	2.20"	20
4.5 Watt	GU5.3	80718	MR16/3M4NW/VWFL/LED	Natural White Dimmable	10-18	5000	72	250	100	40000	1/10	84°	2.20"	20
4.5 Watt	GU5.3	80719	MR16/3M4WW/VWFL/LED	Warm White Dimmable	10-18	2700	82	200	80	40000	1/10	88°	2.20"	20
4.5 Watt	GU5.3	80724	MR16/3M4AMB/NFL/LED	Amber	10-18	-	-	-	-	40000	1/10	22°	2.20"	NA
4.5 Watt	GU5.3	80727	MR16/3M4BLU/NFL/LED	Blue	10-18	-	-	-	-	40000	1/10	22°	2.20"	NA
4.5 Watt	GU5.3	80726	MR16/3M4GRN/NFL/LED	Green	10-18	-	-	-	-	40000	1/10	22°	2.20"	NA
4.5 Watt	GU5.3	80725	MR16/3M4RED/NFL/LED	Red	10-18	-	-	-	-	40000	1/10	22°	2.20"	NA
⊛ 5 Watt	GU5.3	80761	MR16/3M5NW/FL/LED	Natural White Dimmable	10-18	5000	72	330	-	40000	1/10	37°	2.20"	35
⊛ 5 Watt	GU5.3	80763	MR16/3M5WW/FL/LED	Warm White Dimmable	10-18	2700	82	250	480	40000	1/10	37°	2.20"	35
⊛ 5 Watt	GU5.3	80764	MR16/3M5WW/NFL/LED	Warm White Dimmable	10-18	2700	82	250	1150	40000	1/10	20°	2.20"	35
⊛ 5 Watt	GU5.3	80765	MR16/4M5NW/FL/LED	Natural White Dimmable	10-18	5000	72	405	-	40000	1/10	32°	1.97"	35
⊛ 5 Watt	GU5.3	80766	MR16/4M5WW/FL/LED	Warm White Dimmable	10-18	2700	82	300	640	40000	1/10	32°	1.97"	35
⊛ 5 Watt	GU5.3	80767	MR16/4M5WW/NFL/LED	Warm White Dimmable	10-18	2700	82	300	970	40000	1/10	23°	1.97"	35
† 5 Watt	GU5.3	80619	MR16/5NW25/LED	Natural White Dimmable	10-18	5000	72	180	350	40000	1/10	25°	2.00"	35
† 5 Watt	GU5.3	80621	MR16/5NW120/LED	Natural White Dimmable	10-18	5000	72	180	80	40000	1/10	120°	2.00"	35
† 5 Watt	GU5.3	80673	MR16/M5NW25/LED	Natural White Dimmable	10-18	5000	72	220	600	40000	1/10	25°	2.16"	35
† 5 Watt	GU5.3	80614	MR16/M5NW40/LED	Natural White Dimmable	10-18	5000	72	220	450	40000	1/10	40°	2.00"	35
† 5 Watt	GU5.3	80611	MR16/M5WW40/LED	Warm White Dimmable	10-18	2700	82	190	320	40000	1/10	40°	2.00"	35
† 5 Watt	GU5.3	80615	MR16/M5NW120/LED	Natural White Dimmable	10-18	5000	72	220	110	40000	1/10	120°	2.00"	NA
† 5 Watt	GU5.3	80625	MR16/5AMB40/LED	Amber Dimmable	10-18	-	-	-	-	40000	1/10	40°	2.00"	NA
† 5 Watt	GU5.3	80623	MR16/5BLU40/LED	Blue Dimmable	10-18	-	-	-	-	40000	1/10	40°	2.00"	NA
† 5 Watt	GU5.3	80624	MR16/5GRN40/LED	Green Dimmable	10-18	-	-	-	-	40000	1/10	40°	2.00"	NA
† 5 Watt	GU5.3	80622	MR16/5RED40/LED	Red Dimmable	10-18	-	-	-	-	40000	1/10	40°	2.00"	NA
† 6 Watt	GU5.3	80688	MR16/5M6NW25/LED	Natural White Dimmable	10-18	5000	72	385	810	40000	1/10	25°	2.00"	35
† 6 Watt	GU5.3	80689	MR16/5M6WW25/LED	Warm White Dimmable	10-18	2700	82	310	630	40000	1/10	25°	2.00"	35
† 6 Watt	GU5.3	80658	MR16/5M6NW40/LED	Natural White Dimmable	10-18	5000	72	385	620	40000	1/10	40°	2.00"	35
6 Watt	GU5.3	80657	MR16/5M6WW40/LED	Warm White Dimmable	10-18	2700	82	310	500	40000	1/10	40°	2.00"	35
⊛ 6 Watt	GU5.3	80016	MR16/6WW/FL/LED	Warm White Dimmable	10-15	3000	82	350	560	35000	1/10	40°	2.13"	35
6.5 Watt	GU5.3	80746	MR16/6M7NW/FL/LED	Natural White Dimmable	10-18	5000	72	490	1110	40000	1/10	34°	2.09"	50
6.5 Watt	GU5.3	80747	MR16/6M7WW/FL/LED	Warm White Dimmable	10-18	2700	82	390	880	40000	1/10	34°	2.09"	50
6.5 Watt	GU5.3	80752	MR16/6M7WW/NFL/LED	Warm White Dimmable	10-18	2700	82	390	1560	40000	1/10	23°	2.09"	50
6.5 Watt	GU5.3	80751	MR16/6M7NW/NFL/LED	Natural White Dimmable	10-18	5000	72	490	1840	40000	1/10	24°	2.09"	50
PAR16														
3.3 Watt	Med.	80748	PAR16/3NW/NFL/LED	Natural White Dimmable	120	5000	72	160	-	40000	1/6	28°	2.99"	15
3.3 Watt	Med.	80749	PAR16/3WW/NFL/LED	Warm White Dimmable	120	2700	82	145	-	40000	1/6	27°	2.99"	15
3.6 Watt	Med.	80732	PAR16/4AMB/NFL/LED	Amber	120	-	-	-	-	40000	1/6	22°	2.99"	NA

⊛NEW ITEM!

† Available until inventory is depleted. Contact your Halco account representative for substitute.

^ Base down operation only

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
PAR16 cont'd														
3.6 Watt	Med.	80729	PAR16/4RED/NFL/LED	Red	120	-	-	-	-	40000	1/6	22°	2.99"	NA
4.5 Watt	Med.	80730	PAR16/4BLU/NFL/LED	Blue	120	-	-	-	-	40000	1/6	22°	2.99"	NA
4.5 Watt	Med.	80731	PAR16/4GRN/NFL/LED	Green	120	-	-	-	-	40000	1/6	22°	2.99"	NA
† 5 Watt	Med.	80631	PAR16/5AMB/FL/LED	Amber	120	-	-	-	-	40000	1/10	40°	3.35"	NA
† 5 Watt	Med.	80629	PAR16/5BLU/FL/LED	Blue	120	-	-	-	-	40000	1/10	40°	3.35"	NA
† 5 Watt	Med.	80630	PAR16/5GRN/FL/LED	Green	120	-	-	-	-	40000	1/10	40°	3.35"	NA
† 5 Watt	Med.	80628	PAR16/5RED/FL/LED	Red	120	-	-	-	-	40000	1/10	40°	3.35"	NA
6 Watt	Med.	80698	PAR16/6NW/FL/LED2	Natural White Dimmable	120	5000	72	385	-	40000	1/10	40°	3.35"	35
6 Watt	Med.	80697	PAR16/6WW/FL/LED2	Warm White Dimmable	120	2700	82	310	-	40000	1/10	40°	3.35"	35
† 6 Watt	Med.	80720	PAR16/6WW/SP/LED2	Warm White Dimmable	120	2700	82	310	-	40000	1/10	14°	3.35"	35
PAR20														
⊕ 5 Watt	Med.	80002	PAR20/5WW/FL/LED	Warm White Dimmable	120	3000	82	235	-	40000	1/6	40°	3.35"	20
⊕ 5 Watt	Med.	80004	PAR20/5WW/NFL/LED	Warm White Dimmable	120	3000	82	235	-	40000	1/6	25°	3.35"	20
† 7.2 Watt	Med.	80737	PAR20/7NW/FL/LED	Natural White Dimmable	120	5000	72	440	665	40000	1/6	46°	3.43"	35
† 7.2 Watt	Med.	80738	PAR20/7NW/NFL/LED	Natural White Dimmable	120	5000	72	440	1370	40000	1/6	26°	3.43"	35
† 7.2 Watt	Med.	80740	PAR20/7WW/NFL/LED	Warm White Dimmable	120	2700	82	280	1070	40000	1/6	24°	3.43"	35
† 7.2 Watt	Med.	80741	PAR20/7WW/VWFL/LED	Warm White Dimmable	120	2700	82	280	110	40000	1/6	69°	3.43"	35
7.2 Watt	Med.	80736	PAR20/7AMB/NFL/LED	Amber	120	-	-	-	-	40000	1/6	25°	3.43"	NA
† 7.2 Watt	Med.	80734	PAR20/7BLU/NFL/LED	Blue	120	-	-	-	-	40000	1/6	25°	3.43"	NA
† 7.2 Watt	Med.	80735	PAR20/7GRN/NFL/LED	Green	120	-	-	-	-	40000	1/6	25°	3.43"	NA
† 7.2 Watt	Med.	80733	PAR20/7RED/NFL/LED	Red	120	-	-	-	-	40000	1/6	25°	3.43"	NA
† 8 Watt	Med.	80636	PAR20/8NW/NFL/LED	Natural White	120	5000	82	320	-	40000	1/6	25°	3.50"	35
⊕ 8 Watt	Med.	80024	PAR20/8WW/NFL/LED	Warm White Dimmable	120	3000	82	380	930	35000	1/6	25°	3.43"	35
† 8 Watt	Med.	80700	PAR20/8NW/NFL/LED2	Natural White Dimmable	120	5000	82	520	-	40000	1/6	25°	3.50"	35
† 8 Watt	Med.	80699	PAR20/8WW/NFL/LED2	Warm White Dimmable	120	2700	82	400	-	40000	1/6	25°	3.50"	35
† 8 Watt	Med.	80634	PAR20/8WW/VWFL/LED	Warm White	120	2700	82	280	-	40000	1/6	120°	3.50"	35
† 8 Watt	Med.	80642	PAR20/8AMB/FL/LED	Amber	120	-	-	-	-	40000	1/6	40°	3.50"	NA
† 8 Watt	Med.	80640	PAR20/8BLU/FL/LED	Blue	120	-	-	-	-	40000	1/6	40°	3.50"	NA
† 8 Watt	Med.	80639	PAR20/8RED/FL/LED	Red	120	-	-	-	-	40000	1/6	40°	3.50"	NA
8 Watt	Med.	80638	PAR20/8RGB/NFL/LED	Color Changing Red, Green, Blue	120	-	-	-	-	40000	1/6	25°	3.50"	NA
		80649	RGB/REMOTE	Remote Control for Color Changing PAR20 lamp										
PAR30														
⊕ 13 Watt	Med.	80030	PAR30/13NW/FL/LED	Natural White Dimmable	120	5000	82	760	1230	35000	1/6	40°	4.49"	75
⊕ 13 Watt	Med.	80026	PAR30/13WW/FL/LED	Warm White Dimmable	120	3000	82	700	1160	35000	1/6	40°	4.49"	75
⊕ 13 Watt	Med.	80038	PAR30/13NW/NFL/LED	Warm White Dimmable	120	5000	82	760	3250	35000	1/6	25°	4.49"	75
⊕ 13 Watt	Med.	80028	PAR30/13WW/NFL/LED	Warm White Dimmable	120	3000	82	700	-	35000	1/6	25°	4.49"	75
† 14 Watt	Med.	80647	PAR30/14NW/FL/LED/ND	Natural White Non-Dimmable	120	5000	72	710	-	40000	1/6	40°	3.63"	75
† 14 Watt	Med.	80644	PAR30/14WW/FL/LED	Warm White Dimmable	120	2700	82	590	-	40000	1/6	40°	4.61"	75
† 14 Watt	Med.	80644	PAR30/14WW/FL/LED/ND	Warm White Non-Dimmable	120	2700	82	590	-	40000	1/6	40°	3.63"	75
† 14 Watt	Med.	80680	PAR30/14NW/FL/LED2	Natural White Dimmable	120	5000	72	980	-	40000	1/6	40°	4.61"	75
† 14 Watt	Med.	80676	PAR30/14WW/FL/LED2	Warm White Dimmable	120	2700	82	740	-	40000	1/6	40°	4.61"	75
14 Watt	GU24	80758	PAR30/14NW/FL/GU24/LED	Natural White Dimmable	120	5000	72	710	-	40000	1/6	32°	4.65"	75
14 Watt	GU24	80757	PAR30/14WW/FL/GU24/LED	Warm White Dimmable	120	2700	82	590	-	40000	1/6	32°	4.65"	75
† 14 Watt	Med.	80643	PAR30/14WW/NFL/LED	Warm White Dimmable	120	2700	82	590	-	40000	1/6	25°	4.61"	75
† 14 Watt	Med.	80675	PAR30/14WW/NFL/LED2/ND	Warm White Non-Dimmable	120	3100	82	740	-	40000	1/6	30°	3.63"	75
† 14 Watt	Med.	80678	PAR30/14NW/SP/LED2/ND	Natural White Non-Dimmable	120	5000	72	980	-	40000	1/6	10°	4.61"	75
† 14 Watt	Med.	80674	PAR30/14WW/SP/LED2	Warm White Dimmable	120	2700	82	740	-	40000	1/6	10°	4.61"	75
† 14 Watt	Med.	80648	PAR30/14NW/VWFL/LED	Natural White Dimmable	120	5000	72	710	-	40000	1/6	120°	4.61"	75

⊕ NEW ITEM!

† Available until inventory is depleted. Contact your Halco account representative for substitute.

^ Base down operation only.

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	CBCP	Useful Life*	Pkg. Qty.	Beam Spread	MOL	Wattage Equivalent
PAR30 cont'd														
† 14 Watt	Med.	80645	PAR30/14WW/VWFL/LED	Warm White Dimmable	120	2700	82	590	-	40000	1/6	120°	4.61"	75
† 14 Watt	Med.	80645	PAR30/14WW/VWFL/LED/ND	Warm White Non-Dimmable	120	2700	82	590	-	40000	1/6	120°	3.63"	75
PAR30L														
⊛ 9 Watt	Med.	80006	PAR30L/9WW/FL/LED	Warm White Dimmable	120	3000	82	480	-	40000	1/6	40°	4.65"	50
⊛ 9 Watt	Med.	80008	PAR30L/9WW/NFL/LED	Warm White Dimmable	120	3000	82	480	-	40000	1/6	25°	4.65"	50
† 14 Watt	Med.	80655	PAR30L/14WW/NFL/LED	Warm White Long Neck	120	2700	82	590	-	40000	1/6	25°	4.75"	75
PAR36														
⊛ 6.5 Watt	MP Term	80768	PAR36/6WW/WFL/LED2	Warm White, IP67 Rated	10-15	2700	82	260	680	40000	1/6	32°	2.40"	20
⊛ 10 Watt	MP Term	80769	PAR36/10WW/WFL/LED2	Warm White, IP67 Rated	10-15	2700	82	420	920	40000	1/6	32°	2.40"	35
⊛ 18 Watt	MP Term	80770	PAR36/18WW/WFL/LED2	Warm White, IP67 Rated	10-15	2700	82	720	1800	40000	1/6	32°	2.40"	50
PAR38														
⊛ 11 Watt	Med.	80010	PAR38/11WW/FL/LED	Warm White Dimmable	120	3000	82	610	-	40000	1/6	40°	5.12"	60
⊛ 11 Watt	Med.	80012	PAR38/11WW/NFL/LED	Warm White Dimmable	120	3000	82	610	-	40000	1/6	25°	5.12"	60
⊛ 16 Watt	Med.	80036	PAR38/16NW/FL/LED	Natural White Dimmable	120	5000	82	1020	1750	35000	1/6	40°	5.00"	90
⊛ 16 Watt	Med.	80032	PAR38/16WW/FL/LED	Warm White Dimmable	120	3000	82	950	1600	35000	1/6	40°	5.00"	90
⊛ 16 Watt	Med.	80034	PAR38/16WW/NFL/LED	Warm White Dimmable	120	3000	82	950	-	35000	1/6	25°	5.00"	90
† 18 Watt	Med.	80670	PAR38/18WW/FL/LED	Warm White Dimmable	120	2700	82	1020	-	40000	1/6	40°	4.81"	90
R12														
2.6 Watt	BA15d	80756	GBF/3WW/LED	Warm White	10-18	2700	82	145	-	40000	1/10	-	2.52"	20
⊛ 2.6 Watt	BA15s	80701	1383/3WW/LED	Warm White	10-18	2700	82	145	-	40000	1/10	-	2.52"	20
Plastic Wedge														
⊛ 2.5 Watt	Plastic Wedge	80777	3155/2WW/LED	Warm White, IP65 Rated	10-18	3000	82	140	-	40000	1/10	-	2.40"	20

⊛ **NEW ITEM!**

† Available until inventory is depleted. Contact your Halco account representative for substitute.

^ Base down operation only.

■ Represents lamps that are Energy Star approved.

IP65 rating classifies the lamp is protected against the entry of dust in sufficient quantity to interfere with satisfactory operation of equipment and is intended for indoor or outdoor use primarily to provide a degree of protection against hose directed water from all practical directions.

IP67 rating classifies the lamp is protected against the effects of temporary immersion between 15cm (5.9in) and 1m (3.28ft) and is intended for indoor or outdoor use primarily to provide a degree of protection against hose directed water, the entry of water during occasional temporary submersion at a limited depth, and damage from external ice formation.