

FEATURES & SPECIFICATIONS

INTENDED USE — The ACLED combines digital LED lighting and control technologies with a high performance optical system to deliver general ambient lighting for many applications such as schools, offices, and hospitals. High efficacy light engine delivers long life and excellent color, ensuring a superior quality light installation that is highly efficient and sustainable. **Certain airborne contaminants can diminish integrity of acrylic.** [Click here for Acrylic Environmental Compatibility table for suitable uses.](#)

CONSTRUCTION — Housing formed from cold-rolled steel. Housing is painted after fabrication for superior finish.

Smooth hemmed sides and smooth inward formed end flanges for easy handling.

Standard deep regressed door frame with step baffles provides unique architectural appearance. Door frame is painted after fabrication standard. Powder painted rotary cam latches provide easy secure door closure. Integral T-bar clips standard. Acrylic shielding material 100% UV stabilized.

OPTICS — Frosted acrylic tile provides superior efficiency and a clean quiet appearance in the ceiling

ELECTRICAL — Long life LEDs, coupled with high-efficiency drivers, provide superior quantity and quality of illumination for extended service life. ACLED is rated to deliver L80 performance for 50,000 hours. Standard nLight embedded controls continuously monitor system performance, allow for constant lumen management/compensation function, facilitate simple “plug-and-play” network and controls upgrading via Cat-5 cable.

LED Accudrive driver delivers full-range dimming from 0-10V control signal.

Ballast disconnect provided where required to comply with US and Canadian codes

INSTALLATION — Drivers and internal components accessible from floor. LED boards include plug in connectors for easy replacement or servicing. Suitable for direct insulation contact. Suitable for damp location.

LISTINGS — CSA certified to meet U.S. and Canadian standards

WARRANTY — Five-year warranty coverage of luminaries includes fixture construction, LED light engine, driver and nLight control device. Terms and conditions apply.


Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

ACLED



LED
2x4



Specifications

Length: 48 (122.0)

Width: 24 (61.0)

Depth: 3-3/4 (9.5)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 2ACL4 48L D50 LP835 N80

2ACL4	48L	Voltage		D50	Lamp color		Controls		Options	
Series	Lamp type			Driver						
2ACL4 Recessed LED	48L ¹	(blank)	MVOLT (120-277V)	D50 50W ²	LP835	82 CRI, 3500 Kelvin	N100	nLight without lumen management	EL14L	1400 lumen battery pack
					LP840	82 CRI, 4000 Kelvin	N80	nLight with 80% (L80) lumen management		
					LP850	82 CRI, 5000 Kelvin	N100EMG	nLight without lumen management for use with generator supply EM power		
							N80EMG	nLight with 80% (L80) lumen management for use with generator supply EM power		
							NX	Less controls		

nLight® Control Accessories:

Order as separate catalog number. Visit www.sensorswitch.com/nLight for complete listing of nLight controls.


WallPod stations	Model number	Occupancy sensors	Model number
On/Off	nPODM [color]	Standard range 360°, ceiling (PIR / dual tech)	nCM 9 / nCM PDT 9
On/Off & Raise/Lower	nPODM DX [color]	Extended range 360°, ceiling (PIR / dual tech)	nCM 10 / nCM PDT 10
Graphic Touchscreen	nPOD GFX	Wide view (PIR / dual tech)	nWV 16 / nWV PDT 16
Photocell controls	Model number	Cat-5 cable bundles (plenum rated)	Model number
Continuous dimming	nCM ADC	10', 15 pieces per bundle	CATS 10FT
On/Off & Dimming	nCM PC ADC	30', 15 pieces per bundle	CATS 30FT

Notes

- 1 Nominal lumens.
- 2 Nominal wattage.

PHOTOMETRICS

2ACL4 48L D50 LP835 N100, 4,887 delivered lumens, test no. LTL21099, tested in accordance to IESNA LM-79.



Control Functionality

The ACLED comes standard with an embedded nLight® control device called the nIO-LED. This smart device makes each luminaire addressable – allowing it to digitally communicate with other nLight-enabled controls such as dimmers, switches, occupancy sensors, and photocells (see accessory table on page one). This allows for advanced operation and design flexibility ranging from stand-alone rooms to building and campus-wide networks.

Linking devices within a room is easy – simply connect all the nLight-enabled control devices and ACLED luminaires using standard CAT-5 cabling. System power for all control devices is provided directly from the luminaires. This feature greatly reduces the installation time and labor requirements, as there are no line voltage connections to any power/relay packs. Finally, being nLight-enabled offers true plug-and-play convenience as devices and luminaires automatically discover each other and self commission. Visit www.sensorswitch.com/nLight for more information about nLight controls.

Constant Lumen Management

Enabled by the embedded nLight control, the ACLED actively tracks its run-time and manages its light source such that constant lumen output is maintained over system life. Referred to as lumen management, this feature eliminates the energy waste created by the traditional practice of over-lighting.

