

Slot 4 LED and Slot 6 LED from Mark Architectural Lighting

Made-to-Order and Available to Ship in Just Two Days from the Acuity Brands[®] Manufacturing & Distribution Center in Ontario, CA!

Dimming and Controls Options

nLight[®]

The Mark Slot 4 LED and Slot 6 LED are available with on-board nLight digital technology that allows the luminaire to communicate with control devices such as occupancy sensors, photocells and wall stations.

nLight is a networked digital lighting control system that is easy-to-use, easy-to-install and saves energy. With unmatched flexibility, nLight easily scales from one room to an entire campus. Create a lighting control solution that's perfect for your space and need.

eldoLED Options

Mark Slot LED features an eldoLED 0-10V driver as standard, providing smooth, seamless and flicker-free dimming from 2 to 100%. These advanced dimming capabilities save energy and prolong the life of the LED modules while taking full advantage of the LEDs range of dimming.

Key Features

Performance

- 60 lumens/watt (delivered lumens)
- An optional lumen management system provides onboard intelligence that actively manages the LED light source so that constant lumen output is maintained over the system's life, creating a consistently illuminated environment while preventing energy waste.

Luminaires

- Nominal 4" x 4' or 8' units 6" x 4' or 8' units
- Available with a flush or regressed lens
- Linear runs only
- Available in 3,500K CCT

S4LROTM and S4LFOTM, 4" x 4' or 8'

Ordering information

Example: S4LROTM 4FT TG N35GEDR 120 SW N100 WRMDC

Series		Length	Ceiling Trim		Linear LED Output ²		Linear LED Color Temp ²		Driver ²	
S4LROTM ¹	Regressed Lens	4FT 4'	TG	9/16" Flat or Inverted Tee	N	Normal	35	3500K	GEDR Constant Current Driver, 0-10v Dimmable	
S4LFOTM ¹	Flush Lens	8FT 8'	FL	5/8" flange (sheetrock)						
Voltage		Shielding	Integrated Controls		Options		Regional Note			
120	SW	1/8" P95 opal acrylic	N100	N100 nLight without Lumen mgt	PWS901836	6' prewire, 3/8" diameter, 18-gauge, 3 wires	WRMDC West Regional Manufacturing Distribution Center			
277			N80	N80 nLight with 80% Lumen mgt						
			NX	Dimming, No nLight	PWS901846	6' prewire, 3/8" diameter, 18-gauge, 4 wires				
			N100EMG	N100 nLight without Lumen mgt for generator EM power						
			N80EMG	N80 nLight Lumen mgt for generator EM power						

Note

1 Individual units as listed ONLY

2 These three option categories combine to make a single piece of nomenclature as follows: N35GEDR

S6LROTM and S6LFOTM, 6" x 4' or 8'

Ordering information

Example: S6LROTM 4FT TG N35GEDR 120 SW N100 WRMDC

Series		Length	Ceiling Trim		Linear LED Output ²		Linear LED Color Temp ²		Driver ²	
S6LROTM ¹	Regressed Lens	4FT 4'	TG	9/16" Flat or Inverted Tee	N	Normal	35	3500K	GEDR Constant Current Driver, 0-10v Dimmable	
S6LFOTM ¹	Flush Lens	8FT 8'	FL	5/8" flange (sheetrock)						
Voltage		Shielding	Integrated Controls		Options		Regional Note			
120	SW	1/8" P95 opal acrylic	N100	N100 nLight without Lumen mgt	PWS901836	6' prewire, 3/8" diameter, 18-gauge, 3 wires	WRMDC West Regional Manufacturing Distribution Center			
277			N80	N80 nLight with 80% Lumen mgt						
			NX	Dimming, No nLight	PWS901846	6' prewire, 3/8" diameter, 18-gauge, 4 wires				
			N100EMG	N100 nLight without Lumen mgt for generator EM power						
			N80EMG	N80 nLight Lumen mgt for generator EM power						

Note

1 Individual units as listed ONLY

2 These three option categories combine to make a single piece of nomenclature as follows: N35GEDR



Contact Performance Lighting Systems for more information:
controls@performanceltg.com

*Two-day shipment lead-time from order entry for quantities of 100 or less.

Product can meet any and all Title 24 requirements. Must be configured properly. For help with understanding Title 24 requirements, contact your local Acuity Brands agent.