


# WPLED10DC

10 Watt Surface mount or Junction Box LED Wallpack. Equivalent to 70W HPS. IESNA Full Cutoff, Fully Shielded optics. Mount at 7-10'. 12V/24V DC. 5 year warranty.

Color: Bronze

Weight: 3.3 lbs



## LED Info

Watts: 10  
 Color Temp: N/A  
 Color Accuracy: N/A  
 L70 Lifespan: 0  
 LM79 Lumens: 547  
 Efficacy: 0 LPW

## Driver Info

Type: DC Driver 12V/24V DC  
 120V: N/A  
 208V: N/A  
 240V: N/A  
 277V: N/A  
 Input Watts: N/A  
 Efficiency: N/A

## Technical Specifications

### Starting Amps/Operating Amps:

12V DC/3.5A, 24V DC/3.5A

### Finish:

Chip and fade resistant polyester powder coat finish.

### Color Stability:

RAB LEDs exceed industry standards for chromatic stability.

### Color Uniformity:

RAB's range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

### Cold Weather Starting:

The minimum starting temperature is -22F/-30C

### Ambient Temperature:

Suitable for use in 40C (104F) ambient temperatures

### Fixture Efficacy:

41 Lumens per Watt

### Color Accuracy:

92 CRI

### Color Temperature (Nominal CCT):

5250 K (Daylight)

### LED Light Engine:

Multi-chip 10W high output long life LED DC Driver 12V/24V DC

### Heatsink:

Cast aluminum thermal management system for optimal heat sinking. The LPACK is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

### Lumen Maintenance:

The LED will deliver 70% of its initial lumens at 50,000 hours of operation.

### Housing:

Precision die cast aluminum housing, lens frame.

### Mounting:

Junction box.

### California Title 24:

LPACK complies with California Title 24 building and electrical codes.

### Green Technology:

RAB LEDs are Mercury, Arsenic and UV free.

### Patents:

The LPACK design is protected under patents pending in the U.S., Canada, China, Taiwan and Mexico.

### Dark Sky Approved:

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

### For use on LEED Buildings:

IDA Dark Sky Approval means that this fixture can be used to achieve LEED Credits for Light Pollution Reduction.

### IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

### Gaskets:

High Temperature Silicone



WPLED10DC - continued

**Warranty:**

RAB LED fixtures give you peace of mind because both the fixture and light engine components are backed by RAB's 5 Year Warranty. For more information,

**Equivalency:**

The WPLED10 is Equivalent in delivered lumens to a 70W Metal Halide Wallpack.

**Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by IBEW Local 3

**Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010)

**Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

**GSA Schedule:**

This product is suitable for listing on the GSA Schedule of the US General Services in accordance with FAR Subpart 25.4

